Lubriplate®

SYNXTREME HD SERIES

100% Synthetic, Calcium Sulfonate Complex Greases.

Xtreme Protection For Your Precious Metals

Lubriplate® SYNXTREME HD Series Greases

Lubriplate SynXtreme HD and HD/220 Series Advanced Technology Greases provide a level of performance and versatility we could only dream about just a few years ago. Engineered to provide superior performance throughout a wide range of applications and conditions, these super multi-purpose greases can help you significantly reduce, consolidate and simplify your grease inventory. In fact, they may be the only greases you'll ever need.

- Advanced 100% Synthetic, Calcium Sulfonate Complex Formula.
- Xtreme Multi-Purpose, Ideal for a Wide Variety of Applications.
- Excellent Anti-Wear and Extreme Pressure Protection.
- Effective working temperature range -45˚F/-43˚C to 450˚F/232˚C.
- Outstanding Shear Stability, Grease Retains Thickness.
- SYNXTREME FG Series - Same Benefits in NSF H-1 Food Machinery Grade.

The Life Blood of your machinery!

"It's the Film" ®
PREVENTS WEAR and CORROSION
LUBRIPLATE
SUPER-LUBRICATION

Lubriplate® Lubricants

Newark, NJ 07105 / Toledo, OH 43605 / 1-800-733-4755
www.lubriplate.com / LubeXpert@lubriplate.com

Backed By: Lubriplate® ESP

Extra Services Package

- *Complimentary Equipment Surveys*
- *Tech Support*
- *Lubrication Software*
- *Machinery Tags*
- *Follow-Up Lubricant Analysis*
- *Training*

Lubriplate® SynXtreme HD Series Greases

SYNXTREME HD-Series:

Extreme-Duty, Multi-Purpose, High-Temperature, Synthetic, Calcium Sulfonate Complex Greases.

These high performance, extreme-duty, multi-purpose, synthetic, calcium sulfonate complex greases provide unsurpassed anti-wear, and extreme pressure protection. They are highly water resistant and work well over a wide range of temperature extremes and other adverse conditions. Superior shear stability and oxidation resistance provide long lasting protection. Available in 3 NLGI grades for a wide range of applications. SYNXTREME HD-2 is NLGI GC-LB certified for wheel bearing and chassis lubrication. SYNXTREME HD-1/220 and HD-2/220 are formulated with a heavier (ISO 220 Grade) base fluid and are recommended for slow to medium speed bearings and other equipment operating under high temperature conditions.

Specifications

LUBRIPLATE PRODUCT	NLGI DENSITY	OIL VIS. cSt / SUS @ 40˚C / 100˚F	WORKED PENETRATION	RECOMMENDED OPERATING TEMPERATURE RANGE	AW / EP	RUST & OXID. ADDITIVES	WATER RESISTANT
SYNXTREME HD-0	0	100 / 500	355 / 385	-45˚F / -43˚C to 390˚F / 199˚C	AW/EP	YES	YES
SYNXTREME HD-1	1	100 / 500	310 / 340	-45˚F / -43˚C to 440˚F / 227˚C	AW/EP	YES	YES
SYNXTREME HD-2	2	100 / 500	265 / 295	-45˚F / -43˚C to 450˚F / 232˚C	AW/EP	YES	YES
SYNXTREME HD-1/220	1	220 / 1020	310 / 340	-40˚F / -40˚C to 440˚F / 227˚C	AW/EP	YES	YES
SYNXTREME HD-2/220	2	220 / 1020	265 / 295	-40˚F / -40˚C to 450˚F / 232˚C	AW/EP	YES	YES

Packaging Availability / Part Number

Package / Part Number	Cartridges 14.5 oz / 411g	Pail 35 lb / 19.9 kg	1/4 Drum 120 lb / 54 kg	Drum 420 lb / 191 kg
SYNXTREME HD-0	-	L0403-035	L0403-039	L0403-040
SYNXTREME HD-1	L0402-098	L0402-035	L0402-039	L0402-040
SYNXTREME HD-2	L0401-098	L0401-035	L0401-039	L0401-040
SYNXTREME HD-1/220	L0313-098	L0313-035	L0313-039	L0313-040
SYNXTREME HD-2/220	L0312-098	L0312-035	L0312-039	L0312-040

"It's the Film" ® PREVENTS WEAR and CORROSION LUBRIPLATE SUPER-LUBRICATION

Lubriplate® Lubricants

Newark, NJ 07105 / Toledo, OH 43605 / 1-800-733-4755
www.lubriplate.com / LubeXpert@lubriplate.com

Backed By: Lubriplate® ESP Extra Services Package

• Complimentary Equipment Surveys • Tech Support
• Lubrication Software • Machinery Tags
• Follow-Up Lubricant Analysis • Training