



Eliminate Lubrication As A Potential Chemical Hazard In Your HACCP Program.

Simply Use 100% Lubriplate® NSF H-1 Registered Lubricants Throughout Your Plant.

Using Lubriplate H-1 Lubricants throughout your plant not only provides peace of mind, they can significantly simplify your HACCP program by eliminating lubrication as a potential chemical hazard.

- Clean, Safe, Non-Toxic lubrication for all of your machinery.
- NSF H-1 Registered, Food Machinery Grade.
- Manufactured in compliance with ISO 21469 guidelines.
- Formulated with ingredients that comply with FDA Regulations 21 CFR 178.3570 and 21 CFR 172.882 for lubricants with incidental food contact.
- They Meet USDA H-1 safety standards and are authorized for use in federally inspected meat and poultry plants.
- Certified OU Kosher Pareve.



Lubricants You Can Trust From The Team You Can Trust



Lubriplate Lubricants Company

1-800-733-4755 / www.lubriplate.com / LubeXpert@lubriplate.com

Features and Benefits of Lubriplate® Food Grade Lubricants.

Lubriplate's complete line of NSF H-1 Registered, Food Machinery Lubricants is designed to provide total food processing and bottling plant lubrication capability. Formulated from high quality base stocks combined with unique premium, anti-wear additives, these lubricants exceed many performance specifications of conventional H-2 lubricants. All Lubriplate H-1 Lubricants are manufactured with ingredients that comply with FDA regulation 21 CFR 178.3570 for lubricants with incidental food contact. They meet USDA H-1 safety standards and are authorized for use in federally inspected meat and poultry plants. Their use eliminates lubrication as a critical control point in your HACCP program.

FEATURES	BENEFITS
Advanced High-Performance Formulations	Improved machinery life; decreased wear; reduced power consumption; extended lube intervals.
NSF H-1 Registered Products	Assures compliance with USDA / FDA guidelines and HACCP programs.
Multifunctional use	Reduces, consolidates and simplifies lubricant inventories and reduces lubricant misapplication.
Toll Free Technical Support 800-347-5343	Quick response to your lubrication questions.
Complimentary Plant Surveys	Identify opportunities for lubricant inventory consolidation and improvements.
No-charge Oil/Fluid and Grease Analysis	Helps determine lubricant and/or machinery condition and corrective measures needed.

F.D.A. Codes (CFR) which affect lubricants for machinery with incidental food contact.

21.CFR 178-3570	Ingredients used to manufacture H-1 lubricants must comply with this code. / All Lubriplate H-1 products comply with this code.
21.CFR 178-3620	Technical White Mineral Oil as a component of non-food articles intended for use in contact with food. / The FMO Series complies.
21.CFR 172-878	USP White Mineral Oil for direct contact with food. / Lubriplate FMO Series complies with this code.
All of the mineral oil based products in the LUBRIPLATE H-1 range are formulated with USP White Mineral Oil which is both the purest and highest quality base oil any manufacturer can use to formulate H-1 lubricants.	
21.CFR 172-882	Synthetic isoparaffinic hydrocarbons, i.e., PAO base stocks / Lubriplate SFGO Ultra Series, SFL Series and the SYNXTREME FG Series.
21.CFR 182 with 9 subheadings	Substances Generally Recognized As Safe, e.g., zinc oxide and tocopherols (Vitamin E.)

Lubriplate® Application Recommendations

APPLICATIONS	LUBRIPLATE PRODUCT	APPLICATIONS	LUBRIPLATE PRODUCT
<ul style="list-style-type: none"> • GENERAL GREASING NORMAL TEMPERATURES HIGH TEMPERATURES LOW TEMPERATURES • GENERAL OILING • CENTRALIZED GREASING SYSTEMS • SLIDES, CAMS, EXPOSED GEARS • CHAINS, CONVEYORS, WIRE ROPE • ENCLOSED GEAR CASES HELICAL GEARS WORM GEARS • HOT BRAKE BEARINGS • AIR COMPRESSORS RECIPROCATING ROTARY SCREW • AIR LINE SYSTEMS • HYDRAULIC SYSTEMS NORMAL TEMPERATURES LOW TEMPERATURES • HIGH SPEED BEARINGS GREASE OIL • CHEMICAL & CONDENSATE PUMPS GREASE OIL • VACUUM PUMPS 	<p>SYNXTREME FG-2 or FGL-2 SYNXTREME FG-2 or FGL-2 SYNXTREME FG-1 or SFL-1</p> <p>SFGO ULTRA-68 or FMO-350AW</p> <p>FGL-0 or FGL-00</p> <p>PURE TAC</p> <p>SFGO ULTRA-7 or FP-150L</p> <p>SFGO ULTRA-220 or FMO-1100AW SFGO ULTRA-460 or FMO-2400AW</p> <p>SYNXTREME FG-2 or PURE TAC</p> <p>SFGO ULTRA-68 or SFGO ULTRA 100 SFGO ULTRA-32 or SFGO ULTRA 46</p> <p>FMO-85AW or FMO-150AW</p> <p>SFGO ULTRA-68 or FMO-350AW SFGO ULTRA-7 or FMO-85AW</p> <p>SFL-1 or FGL-1 SFGO ULTRA-32 or FMO-150AW</p> <p>SYNXTREME FG-2 or FGL-2 SFGO ULTRA-68 or FMO-350AW</p> <p>SFGO ULTRA-68 or SFGO ULTRA 100</p>	<ul style="list-style-type: none"> • DRAFT & VENTILATING FANS GREASE OIL • STIRRUPS - BOTTLE FILLERS • PEACH PITTERS - CHAIN DRIVES • SEAMING ROLLS, SPINDLES, CHUCKS • COOKERS - CARRIER BEARINGS • COOKER VALVE LUBRICATION (MANZEL LUBRICATORS) • ANGELUS SEAMERS (MANZEL LUBRICATORS) • SIGHT FEED OILERS • ELECTRIC MOTOR BEARINGS • STEAM VALVES & PEELERS • SCRUBBERS GREASE FITTINGS CHAIN DRIVES • FORKLIFTS WHEEL BEARINGS HYDRAULIC OIL CHAIN LIFTS • RUST PREVENTATIVE, LAYING UP • CLEANSING & FLUSHING OIL • PAN DIVIDER OIL • LUBRIPLATE WHITE OILS 	<p>SYNXTREME FG-2 or FGL-2 SFGO ULTRA-68 or FMO-350AW</p> <p>STO-FG</p> <p>FP-150L or FP-150</p> <p>SYNXTREME FG-1 or FGL-1 SYNXTREME FG-2 or PURE TAC</p> <p>FOOD GRADE COOKER OIL SSO-FG 100 or SSO-FG FMO-500AW or FMO-900AW</p> <p>PM-500 or FP-150L</p> <p>SYNXTREME FG-1 or FGL-1 Consult LUBRIPLATE Tech Service 1-800-347-5343</p> <p>SYNXTREME FG-2 or FGL-2 FP-150L or FP-150</p> <p>SYNXTREME FG-2 or PURE TAC SFGO ULTRA-68 or FMO-350AW FP-150L</p> <p>SFGO ULTRA-7 or FMO-350AW</p> <p>PURE FLUSH FMO-85D FMO SERIES</p>

 Synthetic Based Product

 USP Mineral Oil Based Product

Lubriplate Lubricants Company

Newark, NJ 07105 / Toledo, OH 43605 / Phone: 1-800-733-4755 / Website: www.lubriplate.com / E-mail: lubeXpert@lubriplate.com