

**Reliable, Consistent Machinery
Lubrication Is Easy With
The New Perma Nova
Automatic Lubricator
And Lubriplate®
Quality Greases.**

**Introducing The First
Temperature Independent
Electrochemical Lubrication System**

- **Electronic Controlled Unit with Integrated Temperature Compensation.**
- **LCD Display with Easy Pushbutton Programming.**
- **1 - 12 Month Output Settings.**
- **Application Temperature Range -4°F to 140°F.**
- **Volume Size 130cc (4.57 oz).**
- **Pressure Build-up of 6.2 - 6.3 bar (90 psi).**
- **Intrinsically Safe, Explosion Proof ATEX / FM / IP 65 protection.**

**Available Pre-Filled
With These Lubriplate® Greases**

- SynXtreme HD-2 - Extreme-Duty, Synthetic, Calcium Sulfonate Complex Grease**
- Lubriplate No. 1551 - Heavy-Duty, Petroleum Oil-Based, Lithium Complex Grease**
- SynXtreme FG-2/220 - NSF H-1 Registered, Synthetic, Food Grade Grease**
- Lubriplate FGL-1 - USP Mineral Oil-Based, NSF H-1 Registered, Food Grade Grease**



Lubriplate Lubricants Company

1-800-733-4755 / www.lubriplate.com / LubeXpert@lubriplate.com