

Lubriplate® Power Hammer & Chisel Grease.

The Right Lubricant For Heavy-Duty Power Hammers.

- Super Heavy-Duty, Extreme Pressure Grease.
- Fortified with Moly, Copper and Graphite.
- Contains a High Concentration of Total Solids.
- Provides Unsurpassed Anti-Wear Protection.
- Greatly Extends Shaft and Bushing Life.
- Withstands High Temperatures.
- Highly Water Resistant.

Available in 14.5 oz Cartridges - Part No. L0190-098
and 120 lb Drums - Part Number L0190-039

Properties	Test Method	Typical Value
NLGI Grade	-	2
Worked Penetration	ASTM D-217	265 - 295
Grease Type (Thickener)	-	Aluminum Complex
Dropping Point	ASTM D-2265	514°F / 268°C
Four Ball EP Test, OK Load / Weld Load	ASTM D-2596	520 Kg. / 540 Kg.
Base Oil Properties		
Viscosity SUS@100°F	ASTM D-88	1000
Viscosity SUS@210°F	ASTM D-88	73
Flash Point (COC)	ASTM D-92	420°F / 216°C

NLGI- National Lubricating Grease Institute ASTM- American Society of Testing & Materials



High Performance Lubricants

Lubriplate Lubricants Company
Newark, NJ 07105 / Toledo, OH 43605 / Phone: 1-800-733-4755
Website: www.lubriplate.com / E-mail: info@lubriplate.com

Have a
Lubrication
Question?

E-Mail it to:
LubeXpert@lubriplate.com