



Reduce - Consolidate - Simplify

With Lubriplate® Syn Lube Series Super Multi-Purpose Lubricants.

Imagine a series of lubricants so versatile they can replace virtually all of your fluid lubricants. Air compressor fluids, hydraulic oils, gear, bearing & recirculating oils. They all can be replaced with Lubriplate Syn-Lube Fluids.

They Deliver...

- Multi-Application Capability
- Reduced Lubricant Inventories
- Advanced Synthetic Technology
- Extended Lube Intervals
- Superior Performance

Call today to find out more about Lubriplate Syn-Lube Lubricants and our complete line of high performance synthetic lubricants.



Technology You Can Trust From The Team You Can Trust!



Lubriplate Lubricants Company

Newark, NJ 07105 / Toledo, OH 43605 / 1-800-733-4755
www.lubriplate.com / LubeXpert@lubriplate.com

Lubriplate® Syn Lube Series Super Multi-Purpose Fluid Lubricants

Syn Lube Series: Polyalphaolefin (PAO)-Based, 100% Synthetic Multi-Purpose Fluids.

These multi-purpose, 100% synthetic based, zinc-free fluids are formulated with state-of-the-art additives. These fluids provide outstanding performance over extended drain intervals. Syn Lube 22, 32, 46, 68 & 100 are recommended for many types of rotary screw and piston type air compressors, hydraulic systems, blowers, and turbine oil applications. Syn Lube 150, 220, 320, 460, 680 & 1000 are recommended for gearboxes, bearings, chains and recirculating systems.

LUBRIPLATE PRODUCT	PRODUCT PART NO.	ISO GRADE	AGMA NO.	SAE NO.	VIS. cSt @ 40°C / 100°C	VIS. SUS @ 100°F / 210°F	VIS. INDEX	FLASH POINT	FIRE POINT	POUR POINT
SYN LUBE 22	L0968-	22	-	5W	23 / 5	129 / 44	138	420°F / 216°C	470°F / 243°C	-70°F / -57°C
SYN LUBE 32	L0970-	32	-	10	32 / 6	160 / 47	136	470°F / 243°C	505°F / 263°C	-70°F / -57°C
SYN LUBE 46	L0971-	46	1	20	44 / 8	223 / 52	138	485°F / 250°C	550°F / 288°C	-65°F / -54°C
SYN LUBE 68	L0972-	68	2	20	66 / 10	314 / 58	138	515°F / 267°C	580°F / 304°C	-60°F / -51°C
SYN LUBE 100	L0973-	100	3	30	110 / 15	523 / 66	142	530°F / 277°C	590°F / 310°C	-55°F / -48°C
SYN LUBE 150	L0974-	150	4	80W-90	151 / 20	762 / 97	156	510°F / 266°C	555°F / 291°C	-60°F / -51°C
SYN LUBE 220	L0975-	220	5	90	216 / 26	1088 / 128	155	510°F / 266°C	555°F / 291°C	-50°F / -46°C
SYN LUBE 320	L0976-	320	6	80W-140	311 / 34	1557 / 161	155	505°F / 263°C	550°F / 288°C	-50°F / -46°C
SYN LUBE 460	L0977-	460	7	140	446 / 45	2143 / 211	156	505°F / 263°C	550°F / 288°C	-45°F / -43°C
SYN LUBE 680	L0978-	680	8	-	623 / 57	3289 / 275	157	500°F / 260°C	545°F / 285°C	-45°F / -43°C
SYN LUBE 1000	L0979-	1000	8A	-	950 / 77	4900 / 372	157	500°F / 260°C	545°F / 285°C	-35°F / -37°C

Syn Lube 22 through 100 is available in Pails and Drums. Syn Lube 150 through 1000 is available in Jugs, Pails, 1/4 Drums & Drums. See below for more information.

Syn Lube HD Series: Heavy-Duty, Extreme Pressure, Polyalphaolefin (PAO)-Based, 100% Synthetic Fluids.

These heavy-duty, zinc free, extreme pressure, 100% synthetic based, fluid lubricants are designed for applications where an extreme pressure synthetic fluid is required. They deliver outstanding extreme pressure protection, excellent anti-wear properties and very low coefficients of friction, resulting in lower operating temperatures, reduced power consumption and longer equipment life. Excellent thermal stability and oxidation resistance increases service life, providing extended drain intervals. Compatible with a broad range of seals. Syn Lube HD 220 and 460 pass 12 stages of the FZG Test.

LUBRIPLATE PRODUCT	PRODUCT PART NO.	ISO GRADE	AGMA NO.	SAE GEAR OIL NO.	VIS. cSt @ 40°C / 100°C	VIS. SUS @ 100°F / 210°F	VIS. INDEX	FLASH POINT	FIRE POINT	POUR POINT
SYN LUBE HD 150	L1000-	150	4 EP	80W-90	162 / 21	816 / -	154	540°F / 282°C	590°F / 310°C	-60°F / -51°C
SYN LUBE HD 220	L1001-	220	5 EP	90	199 / 25	988 / -	154	540°F / 282°C	580°F / 304°C	-55°F / -48°C
SYN LUBE HD 320	L1002-	320	6 EP	80W-140	310 / 35	1545 / -	157	540°F / 282°C	585°F / 307°C	-50°F / -46°C
SYN LUBE HD 460	L1003-	460	7 EP	140	440 / 47	2191 / -	164	550°F / 288°C	585°F / 307°C	-50°F / -46°C
SYN LUBE HD 680	L1004-	680	8 EP	-	705 / 68	3384 / -	170	555°F / 291°C	580°F / 304°C	-45°F / -43°C

Syn Lube HD Series Lubricants are available in Jugs, Pails, 1/4 Drums & Drums. See below for more information.

Mobil SHC Fluid Series / Lubriplate® Syn Lube Series Interchange

MOBIL SHC SERIES	ISO VIS. GRADE	LUBRIPLATE SYN LUBE SERIES	MOBIL SHC SERIES	ISO VIS. GRADE	LUBRIPLATE SYN LUBE SERIES
SHC 524	32	SYN LUBE 32	SHC 634	460	SYN LUBE 460
SHC 525	46	SYN LUBE 46	SHC 636	680	SYN LUBE 680
SHC 526	68	SYN LUBE 68	SHC 639	1000	SYN LUBE 1000
SHC 624	32	SYN LUBE 32	MOBILGEAR SHC 150	150	SYN LUBE HD 150
SHC 626	68	SYN LUBE 68	MOBILGEAR SHC 220	220	SYN LUBE HD 220
SHC 627	100	SYN LUBE 100	MOBILGEAR SHC 320	320	SYN LUBE HD 320
SHC 629	150	SYN LUBE 150	MOBILGEAR SHC 460	460	SYN LUBE HD 460
SHC 630	220	SYN LUBE 220	MOBILGEAR SHC 680	680	SYN LUBE HD680
SHC 632	320	SYN LUBE 320			

Packaging Containers

Lubriplate Syn Lube Series Fluids are available in a variety of packages including: jugs, pails, drums and refillable bulk container bins. The chart below indicates product packaging availability and package part number suffix. Add the package part number suffix to the product part number.

Not all products are available in every package size.



PRODUCT / PACKAGE PART NO. SUFFIX	4 / JUGS 1 GAL. / 3.79 L	PAIL 5 GAL. / 18.9 L	QTR. DRUM 16 GAL. / 60.5 L	FULL DRUMS 55 GAL. / 208 L.	REFILLABLE OR DISPOSABLE BINS.**
Lubriplate Syn Lube Series Fluids	-057	-060	-061	-062	•

**For size, package part number suffix and price information on Bulk Bins call 800-733-4755.