



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**

Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**

Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**

Phone: 1-800-733-4755

**LUBRIPLATE MULTI-LUBE "A"**

**LUBRIPLATE Multi-Lube "A"** is an anhydrous calcium, NLGI No. 2 grade, non-corrosive, extreme pressure, water resistant, multi-purpose lubricant with a workable range of -20°F to 210°F. **LUBRIPLATE Multi-Lube "A"** is recommended for both plain and anti-friction bearings, cams, slides and open gears. This lubricant is especially suited for wet applications as it is very resistant to moisture and many other liquid contaminants.

**Typical Tests**

|                           |                   |
|---------------------------|-------------------|
| Type of Base              | Anhydrous Calcium |
| Worked Penetration @ 77°F | 265 to 295        |
| NLGI No.                  | 2                 |
| ASTM Dropping Point       | 280°F/138°C       |
| Mineral Oil Viscosity     |                   |
| SUS @ 100°F               | 500               |
| cSt @ 40°C                | 95                |
| Oxidation Stability       | Excellent         |
| Color                     | Beige             |
| Character                 | Smooth            |

**LUBRIPLATE Multi-Lube "A"** is available as follows:

**Packaging Available**

35 lb. Pail  
120 lb., Quarter Size, Drum  
430 lb., Full Size, Drum

**Part No.**

L0183-035  
L0183-039  
L0183-040