



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**

Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**

Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**

Phone: 1-800-733-4755

LUBRIPLATE MO-LITH No. 2

LUBRIPLATE Mo-Lith No. 2 is exactly what the name indicates -- a moly-lithium lubricant -- containing Technical Fine Molybdenum Disulfide. The use of moly has been widely acclaimed by various members in the lubricant field; however, unless the correct amount is used, it has little affect on the end result. Likewise, the base grease that carries the moly must be of premium quality or the benefits are not forthcoming. In LUBRIPLATE Mo-Lith No. 2, we have compounded the optimum percentage of moly for the greatest performance

Typical Tests

Type of Thickener	Lithium
NLGI No	2
Worked Penetration Range @ 77°F	265 to 295
ASTM Dropping Point	350°F/177°C
Mineral Oil Viscosity	
SUS @ 100°F	600
cSt @ 40°C	112
Color	Steel Gray
Contains Molybdenum Disulfide	

ADVANTAGES

- Anti-wear/extreme pressure reinforced by the addition of Molybdenum Disulfide (MoS<sub>2</sub>).
- Non-corrosive.
- High water resistance.

<u>Packaging Available</u>	<u>Part No.</u>
Carton, 24/14 oz Cans	L0180-001
Carton, 6/6 lb. Cans	L0180-006
35 lb. Pail	L0180-035
120 lb., Quarter Size, Drum	L0180-039
430 lb., Full Size, Drum	L0180-040
Carton, 40/14-½ oz. Cartridges	L0180-098

Printed in USA  
Revised 4-15-08