



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**

Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**

Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**

Phone: 1-800-733-4755

LUBRIPLATE Lithplex High Temperature Brick Grease

LUBRIPLATE Lithplex Brick Grease is recommended to meet the lubrication requirements of open slot or open well type bearings where the brick grease rides directly on the bearing shaft. The rotating motion of the bearing shaft wipes a film of lubricant onto the bearing surfaces keeping it properly lubricated.

LUBRIPLATE Lithplex Brick Grease comes in 4-lb. Bricks (12 Bricks per Case). These Bricks are easily cut into smaller pieces to place in the bearing opening. The size of the piece should be small enough to allow freedom of movement of the block while riding on the bearing surface. From time to time, it is also a good practice to turn or rotate these pieces. Also, do not over load or over pack the bearing opening or slot.

Applications for LUBRIPLATE Lithplex Brick Grease are commonly found at rock quarries and paper mills. Its 525°F Dropping Point is a major advantage.

Typical Tests

Unworked Penetration @ 77°F	45 - 75
Dropping Point	525°F/274°C
Mineral Oil Base Viscosity	
SUS @ 40°C	1400
SUS @ 100°C	90 - 110
Viscosity Index	85
Soap	Lithium Complex
% of Thickener	18 - 22
Color	Amber
Texture	Smooth
<u>Packaging Available</u>	<u>Part No.</u>
48 lb. Carton (12 - 4-lb. Bricks)	L0133-038