



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE SPECIAL AUTO-MARINE GREASE

LUBRIPLATE Special Auto-Marine Grease is an NLGI 2 polymer type lubricant specifically designed for automotive and marine applications of all types. This lithium 12-hydroxy stearate grease is extremely shear stable and resistant to both fresh and salt water, making it the ideal lubricant for all marine and automotive needs.

Marine uses include all pressure fitting applications including boat trailer wheel bearings, winch gears, deck machinery, ground tackle and turn-buckles.

Automotive applications include chassis, king pins, steering knuckles, bucket pins, ball joints and universal joints.

ADVANTAGES:

- Excellent extreme pressure/anti-wear properties.
- Extremely shear stable.
- High temperature characteristics.
- Very good sealing properties to keep out water and dirt.
- Outstanding resistance to fresh and salt water.
- Tenacious and adhesive to increase stay-put properties.

Typical Tests

Type of Base	Lithium 12-hydroxy Stearate
Worked Penetration Range	265 - 295
NLGI No.	2
ASTM Dropping Point	400°F+/205°C+
Mineral Oil Viscosity	
SUS @ 100°F	1250
cSt @ 40°C	237
SUS @ 210°F	95
cSt @ 100°C	19
Timken EP Test	
OK Load	60 lbs.
Four Ball EP Test	
OK Load	370 kg.
Load Wear Index	64.3
Corrosion Prevention (ASTM D-1743)	1,1,1
Copper Corrosion (ASTM D-130)	1a
Oxidation Stability (ASTM D-942)	3 psi 100 hours
Water Washout @ 175°F (ASTM D-1264)	1.5%
Appearance	Tacky, beige

(over)

LUBRIPLATE Special Auto-Marine Grease is available in the following packaging:

<u>Part No.</u>	<u>Packaging Available</u>
L0206-001	Carton, 24/14 oz. Cans
L0206-098	Carton, 40/14½ oz. Cartridges

Printed in USA
Revised 4-15-08