



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

#### Sales, Service & Distribution Center

Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

#### Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

#### Sales and Tech Service Support

Phone: 1-800-733-4755

### LUBRIPLATE SPECIAL MARINE GREASE

LUBRIPLATE Special Marine Grease is an NLGI 2 polymer type lubricant specifically designed for marine applications of all types. This lithium 12-hydroxy stearate grease is extremely shear stable and resistant to both fresh and salt water, making it the ideal lubricant for all marine needs.

Uses include all pressure fitting applications including boat trailer wheel bearings, winch gears, deck machinery, ground tackle and turnbuckles.

#### Advantages:

- Excellent extreme pressure/anti-wear properties.
- Extremely shear stable.
- High temperature characteristics.
- Very good sealing properties to keep out water and dirt.
- Outstanding resistance to fresh and salt water.
- Tenacious and adhesive to increase stay-put properties.

#### Typical Tests

Type of Base	Lithium 12-hydroxy Stearate
Worked Penetration Range	265 - 295
NLGI No.	2
ASTM Dropping Point	400°F+/205°C+
Mineral Oil Viscosity	
SUS @ 100°F	1200
cSt @ 40°C	237
SUS @ 210°F	95
cSt @ 100°C	19
Timken EP Test	
OK Load	60 lbs.
Four Ball EP Test	
OK Load	370 kg.
Load Wear Index	64.3
Corrosion Prevention (ASTM D-1743)	1,1,1
Copper Corrosion (ASTM D-130)	1a
Oxidation Stability (ASTM D-942)	3 psi 100 hours
Water Washout @ 175°F (ASTM D-1264)	1.5%
Appearance	Tacky, beige

#### Part No.

#### Packaging Available

L0206-001  
\*L0206-098

Carton, 24/14 oz. Cans  
Carton, 40/14½ oz. Cans (Note: This packaging sold as Special Auto/Marine Grease only)