



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**

Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**

Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**

Phone: 1-800-733-4755

LUBRIPLATE SPRAY-LUBE "A"

MULTI-PURPOSE WHITE LITHIUM SPRAY

LUBRIPLATE Spray-Lube "A" is a multi-purpose, white, medium density lithium grease with exceptional penetrating qualities. The convenient aerosol can, which sprays like a fluid but congeals to a grease, puts an end to messy open cans and dirty grease forever. The handy extension spout gets to those hard-to-reach places allowing pinpointing of the lube to minimize waste.

Unlike many lubricants, LUBRIPLATE Spray-Lube "A" is unaffected by moisture, most chemicals and acids, and will not run, wash off or dry up. Excellent where no grease fittings exist and where tolerances are close and where longer lasting lubrication is desirable.

LUBRIPLATE Spray-Lube "A" may be safely used within temperature ranges of from -10°F to 275°F. A few of the hundreds of possible uses are:

**Home**

Toys, guns, reels, clocks, appliances, skates, hinges, faucet valves, window regulators, garage doors and openers, bicycles, mowers, garden tools, recliners, drawer slides, shop tools, automotive hood and truck releases, ashtray slides, door hinges, cables, battery terminals, accelerator hinges.

**Office**

Typewriters, filing cabinets, adding machines and calculators, duplicating equipment, swivel chairs.

**Industry**

Lightly-loaded open gears, cams, couplings, slides, bearings, bushings, lift truck masts, controls.

**Recreation**

Boat fittings and linkage, golf carts, pin setters, campers, trailers, motorcycles, snowmobiles.

(over)

LUBRIPLATE Spray-Lube "A" Multi-Purpose White Lithium Spray

**Typical Base Grease Properties**

Type of Soap	Lithium
NLGI No.	1
Worked Penetration Range @ 77 F	310/340
ASTM Dropping Point	380°F 193°C
Mineral Oil Viscosity SUS @ 100°F cSt @ 40°C	750 135
Color	White

Packaging Available

Carton, 12/11 oz. Aerosol Cans

Part Numbers

L0034-063