



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE LTR-2

LUBRIPLATE LTR-2 is a RED lithium complex grease that can be used for a variety of industrial, automotive and heavy-duty construction applications. This rugged, extreme pressure lubricant can withstand higher operating temperatures than traditional lithium multi-purpose greases as well as most lithium complex greases.

LUBRIPLATE LTR-2 is tacky, adhesive and very water resistant. The film strength and shear stability of this product is exceptional resulting in wear reduction and long lubricant life.

LUBRIPLATE LTR-2 provides outstanding lubrication in a variety of applications including:

Automotive (including the fleet and truck operator)

Marine

Construction

Logging

Mining

Industrial

(Over)

Typical Characteristics

LUBRIPLATE LTR-2

Type of Base	Lithium Complex
NLGI Grade (ASTM D-217)	2
Appearance	Tacky, Red, Smooth
Base Oil Properties	
Kinematic Viscosity @ 40°C	460 cSt.
Kinematic Viscosity @ 100°C	31 cSt.
ISO VG	460
Dropping Point, °F/°C (ASTM D-2265)	505°F/263°C
Four Ball Wear (ASTM D-2266) 40 kg. 1200 rpm, 1 hr. @ 167°F	0.52 mm
Four Ball EP Test (ASTM D-2596)	620 kg. OK Load
Oil Separation (ASTM D-1742)	0.11 % by weight
Corrosion (ASTM D-130) 3 hours	1a
Water Washout (ASTM D-1264) @ 175°F	<5 %
Bearing Corrosion (ASTM D-1743)	Pass, No Corrosion
Lincoln Ventmeter Testing	70°F 325 psig 30°F 680 psig 0°F 1,050 psig

Packaging Availability

LUBRIPLATE LTR-2

35 lb. Pail	L0167-035
120 lb. Drum	L0167-039
400 lb. Drum	L0167-040
Carton 40/14.5 oz. Cartridges	L0167-098