



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**  
Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**  
Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**  
Phone: 1-800-733-4755

## LUBRIPLATE SYNFLUSH

(\*NSF H-2 Pending)

**LUBRIPLATE SYNFLUSH** is a premium quality, pure synthetic fluid designed to clean and dissolve varnish/deposits found in rotary screw and reciprocating type air compressors while the compressor is in operation. It is compatible with petroleum/mineral oils as well as all **LUBRIPLATE** Synthetic Compressor Fluids and most other synthetic fluids. Contact us for compatibility verification.

**LUBRIPLATE SYNFLUSH** is also designed for flushing compressors converting from petroleum/mineral oil to synthetic fluids. The flushing procedure removes the remaining petroleum oil that is unable to be removed by draining alone as well as cleaning the compressor prior to introducing the new synthetic fluid.

**LUBRIPLATE SYNFLUSH** can also be used to clean hydraulic systems, gearboxes and reducers, FRL's (Airline Oilers) and close looped circulating oil systems.

**LUBRIPLATE SYNFLUSH** is not intended for automotive/diesel applications such as cleaning fuel injectors or crankcases.

Contact **LUBRIPLATE** @ 800-347-5343 for procedural assistance.

### Performance Characteristics & Benefits

- Removes varnish and carbon deposits, which greatly improves compressor efficiency and life expectancy.
- Compatible with petroleum base oils as well as all **LUBRIPLATE** Synthetic Compressor Fluids.
- Can be used in its pure form in all types of air compressors up to 500 hours.
- Contains no hazardous chemicals.
- Offers excellent thermal and oxidative stability.
- Provides excellent solubility, solvency and cleaning capabilities.

<u>Physical Characteristics</u>	<u>ASTM Test Method</u>	<u>Typical</u>
Viscosity @ 40°C cSt	D-445	27
@ 100°C cSt	D-445	5.35
Viscosity Index	D-2270	135
Flash Point; °C (COC)	D-92	243
Fire Point; °C (COC)	D-92	282
Pour Point; °C	D-97	-60
Specific Gravity	D-4052	0.909

(Continued)

**LUBRIPLATE SYNFLUSH:**

**Packaging Available**

Carton 12/1 Quart Plastic  
Carton 4/1 Gallon Jugs  
5-Gallon Pail  
55-Gallon Drum

**Part Numbers**

L0962-054  
L0962-057  
L0962-060  
L0962-062

Printed in USA  
Revised 5-1-08