



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE SUPER CHAIN OIL

LUBRIPLATE Super Chain Oil is a high viscosity, tenacious type, high flash oil containing micro-fine graphite to provide smokeless lubrication of oven chains and other heavy-duty chain operations throughout a wide temperature operating range. The high flash point of 550°F (288°C) and the fact that it does not smoke at elevated temperatures, makes it ideal as an oven chain lubricant.

LUBRIPLATE Super Chain Oil is recommended for bakery ovens, drying ovens and other type ovens where the temperature does not exceed 450°F. It is also recommended for all other types of heavy-duty chain operations such as floor chain conveyors, assembly lines, warehouse distribution lines, car washes and similar operations. LUBRIPLATE Super Chain Oil can be fed through automatic lubricators that can handle a SAE 140 grade lubricant. It can be brushed on, swabbed and drip fed.

Typical Tests

| | |
|------------------------------|---------|
| Viscosity SUS @ 100°F | 2600 |
| cSt @ 40°C | 497 |
| Viscosity SUS @ 210°F | 155 |
| cSt @ 100°C | 32 |
| ISO Grade | 460 |
| API Gravity | 27.4 |
| Flash Point °F/°C | 550/288 |
| Fire Point °F/°C | 625/330 |
| Pour Point °F/°C | 5/-15 |
| Contains micro-fine graphite | |

LUBRIPLATE Super Chain Oil is available in the following:

Packaging Available

Part No.

| | |
|-------------------------|-----------|
| Carton, 4/1 gallon jugs | L0857-057 |
| 5 gallon pail | L0857-060 |
| 16 gallon drum | L0857-061 |
| 55 gallon drum | L0857-062 |