



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE No. 72-C Oil

USDA H-2 Authorized*

LUBRIPLATE No. 72-C Oil was developed specifically for the lubrication of steam peelers where an SAE 90 grade oil is recommended. The emulsifying and wetting agents provide an oiliness film on all the moving plates and dies that prevents chatter in these areas. LUBRIPLATE No. 72-C Oil is compounded with additives that impart a load-carrying film on the lubricated surfaces, provides corrosion resistance, and reduces oxidation and sludge. LUBRIPLATE No. 72-C Oil is also an excellent steam cylinder oil for any applications requiring an SAE 90 grade.

Typical Tests on LUBRIPLATE No. 72-C Oil are as follows:

Viscosity @ 210°F	75 SUS
@ 100°C	13 cSt
Viscosity @ 100°F	750 SUS
@ 40°C	151 cSt
ISO Grade	150
Approximate SAE No.	90
Flash Point	490°F/254°C
Fire Point	520°F/271°C
Gravity	28.0

LUBRIPLATE No. 72-C Oil is available in the following:

<u>Packaging Available</u>	<u>Part No.</u>
55 gallon drum	L0703-062

*Authorized by USDA for use in federally inspected meat and poultry plants. USDA H-2 lubricants may be used as a lubricant or anti-rust agent on equipment in which there is no possibility of the lubricated part contacting the edible product.