



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

LUBRIPLATE STO-4

USDA H-2 Authorized*

LUBRIPLATE STO-4 is a special compounded oil recommended for the lubrication of stirrups on bottle filling machines. LUBRIPLATE STO-4 has excellent emulsifying properties to provide a lubricating film on the metal surfaces even in the presence of excessive moisture. LUBRIPLATE STO-4 is also compounded with detergent type additives to keep the metal surfaces from building up with undesirable residues.

Typical Tests on LUBRIPLATE STO-4 are as follows:

| | |
|-------------------|-------------|
| Viscosity @ 100°F | 255 SUS |
| @ 40°C | 45 cSt |
| ISO Grade | 46 |
| API Gravity | 23.8 |
| Color | L-3.5 |
| Flash Point | 320°F/160°C |
| Fire Point | 400°F/204°C |
| Pour Point | -30°F/-34°C |

LUBRIPLATE STO-4 is available in the following:

| <u>Packaging Available</u> | <u>Part No.</u> |
|----------------------------|-----------------|
| 5 gallon pail | L0860-060 |
| 55 gallon drum | L0860-062 |

*Authorized by USDA for use in federally inspected meat and poultry plants. USDA H-2 lubricants may be used as a lubricant or anti-rust agent on equipment in which there is no possibility of the lubricated part contacting the edible product.

MEYER 24 THRU 72 VALVE BOTTLE FILLERS &
MEYER 88 VALVE HIGH SPEED BOTTLE FILLER

