



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

LUBRIPLATE STO-FG

*NSF H-1 Registered

"This product is certified OU Kosher Pareve"

"This product is Halal certified"

LUBRIPLATE STO-FG is a special compounded oil recommended for the lubrication of stirrups on bottle filling machines. LUBRIPLATE STO-FG has excellent emulsifying properties to provide a lubricating film on the metal surfaces even in the presence of excessive moisture. LUBRIPLATE STO-FG is also compounded with dispersant type additives to keep the metal surfaces from building up with undesirable residues. This anti-wear oil is designed for areas of "incidental contact" requiring a USDA H-1 authorized* product.

Typical Tests

Viscosity SUS @ 100°F	350
cSt @ 40°C	67
ISO	68
SAE Viscosity	20
API Gravity	29.0
Color	0.0
Flash, °F/°C	425/219
Fire, °F/°C	485/252
Pour Point, °F/°C	-15/-26
Four Ball Wear Test 40 Kg, 1200 rpm 167°F, 1 Hour Average Wear Scar Diameter, mm	.36

LUBRIPLATE STO-FG is available in the following packaging:

<u>Packaging</u>	<u>Part No.</u>
5 gallon pail	L0863-060
55 gallon drum	L0863-062

***NSF H-1 Registration No. 126120**
(Meets USDA 1998 Guidelines)

*Authorized by NSF for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

*NSF – National Sanitation Foundation

Manufactured with ingredients that comply with FDA 21 CFR 178.3570.

Printed in USA
Revised 4/21/08

(Over)

MEYER 24 THRU 72 VALVE BOTTLE FILLERS &
MEYER 88 VALVE HIGH SPEED BOTTLE FILLER

