



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE PM-500

*NSF H-1 Registered

"This product is certified OU Kosher Pareve"

"This product is Halal certified"

LUBRIPLATE PM-500 contains emulsifying agents, which wet the lubricated surfaces and provide an oiliness film for moving parts.

LUBRIPLATE PM-500 has been and is being used, very successfully, in pear machines and other applications where a USDA H-1 authorized* white oil is required. LUBRIPLATE PM-500 is specially suited for water conditions existing in the machinery operation.

Typical Tests

Viscosity SUS @ 100°F	530
cSt @ 40°C	101
Viscosity SUS @ 210°F	63
cSt @ 100°C	10.8
API Gravity	28.7
Color	0.0
Flash Point, °F/°C	420/216
Fire Point, °F/°C	485/252
Pour Point, °F/°C	-5/-21
SAE Viscosity	30
ISO Viscosity	100

Packaging Available

35 lb. drum
120 lb. drum
405 lb. drum

Part No.

L0192-035
L0192-039
L0192-040

***NSF H-1 Registration No. 126122**
(Meets USDA 1998 Guidelines)

*Authorized by NSF for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

*NSF – National Sanitation Foundation

Manufactured with ingredients that comply with FDA 21 CFR 178.3570.

Printed in USA
Revised 4/21/08