



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE SFGO Ultra 7 Synthetic Chain & Penetrating Fluid

*NSF H-1 Registered

“This product is certified OU Kosher Pareve”

LUBRIPLATE SFGO Ultra 7 Synthetic Chain & Penetrating Fluid is a pure PAO-type synthetic, NSF H-1 registered product with an effective operating temperature range from -25°F to +250°F. It is an outstanding product to lubricate chains and bearings operating in the food, beverage and pharmaceutical processing industries. It will penetrate and protect against rust and corrosion. It will also keep chains clean.

Typical Tests

Viscosity -	
SUS @ 100°F	51
SUS @ 210°F	34
cSt @ 40°C	7.63
cSt @ 100°C	2.37
Viscosity Index	137
Pour Point °F/°C	-75/-60
Flash Point °F/°C	320/160
Fire Point °F/°C	350/176
API Gravity	43.6
Color	0.0
Four-Ball Wear Test	
Average Wear Scar Diameter	.4 mm
SAE Grade	5W
ISO Viscosity Grade	7

Packaging Available

Carton, 12/11 oz. Aerosol Cans

Part No.

L0912-063

"The **LUBRIPLATE SFGO Ultra 7 Synthetic Chain & Penetrating Fluid** contains no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMEA/410/01 Rev. 2, October 2003".

*NSF (National Sanitation Foundation) H-1 Registration No. **136601**

*Authorized by NSF for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

Manufactured with ingredients that comply with FDA 21 CFR 178.3570.

Printed in USA
Revised 7/9/09