



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE Pure Flush

*NSF H-1 Registered

“This product is certified OU Kosher Pareve”

“This product is Halal Certified”

LUBRIPLATE Pure Flush is a lubricating, flushing and cleansing oil that can be used in food, beverage and pharmaceutical processing plants in any area where there is a possibility of exposure of the lubricated machinery part(s) to edible products.

LUBRIPLATE Pure Flush is a non-drying lubricating cleanser that can be used along with the existing lubricant in order to clean equipment of carbonaceous debris, sludge, dirt, etc., without dismantling machinery. This will save on labor costs, downtime, replacement parts, etc.

LUBRIPLATE Pure Flush can be used to clean and flush bearings, gear cases, hydraulic systems, centralized lubricating systems, chain and air lines/air tools.

While LUBRIPLATE Pure Flush has excellent cleaning capabilities and load-carrying properties, it should always be used along with the existing lubricant at recommended treat levels for flushing and cleansing.

LUBRIPLATE Pure Flush is a petroleum hydrocarbon based product. It is fully compatible with other petroleum-based lubricants such as USP White Mineral Oil, Technical White Oil, Paraffinic or Naphthenic based mineral oils. LUBRIPLATE Pure Flush is also compatible with synthetic fluids, which are known to be compatible with petroleum-based products such as polyalphaolefin (PAO) based products. LUBRIPLATE Pure Flush is also compatible with seals and elastomers, which are known to be compatible with petroleum based lubricants. (For any questions regarding compatibility, please contact LUBRIPLATE Technical Services.)

Please see instructional bulletin 8-20A for more details.

Typical Tests

Viscosity	
SUS at 100°F	50
SUS at 210°F	32
cSt at 40°C	7
cSt at 100°C	1.8
Flash Point °F/°C	210/99
Fire Point °F/°C	220/104
Pour Point °F/°C	-35/-37
API Gravity	40.0
Color	0.0
Aniline Point °F/°C	220/104
Four Ball Wear Test	
Average Wear Scar Diameter	0.60 mm

(Over)

LUBRIPLATE Pure Flush

<u>Packaging Available</u>	<u>Part No.</u>
Ctn., 12/1 Plastic Quarts	L0816-054
Ctn., 4/1 Gallon Jugs	L0816-057
5 Gallon Pail	L0816-060
16 Gallon Drum	L0816-061
55 Gallon Drum	L0816-062

*Authorized by NSF for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

*NSF H-1 Registration No. 126121
(Meets USDA 1998 Guidelines)

*NSF – National Sanitation Foundation

Manufactured with ingredients that comply with FDA 21 CFR 178.3570.

Printed in USA
Revised 1/2/08