



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**

Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**

Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**

Phone: 1-800-733-4755

## LUBRIPLATE PURE TAC

\*NSF H-1 Registered

"This product is certified OU Kosher Pareve"

"This product is Halal certified"

LUBRIPLATE Pure Tac is a food grade, NSF H-1 Registered\* grease designed for applications subjected to chemically treated water, heat and steam in food and beverage processing plants and canneries. Because of its extremely tacky and adhesive characteristics, it is also an excellent open gear grease. Pure Tac is recommended for all types of medium to slow speed bearings. Also, because of its outstanding resistance to water washout, Pure Tac is the ideal grease for hydrostatic cooker chains.

### Typical Characteristics

Thickener	Aluminum Complex
NLGI No	2
Penetration Range	265 to 295
Penetration 60 Strokes Worked	273
Penetration 10,000 Strokes Worked	271
Penetration 100,000 Strokes Worked	270
Dropping Point, °F/°C	520/271
Four Ball EP Test OK Load	200 kgs.
Timken EP Test OK Load	25 lbs.
Water Washout @ 175°F	1.25%
Lincoln Ventmeter Test	
@ 77°F	550 psig
@ 30°F	825 psig
@ 0°F	Not Pumpable

(Over)

## **LUBRIPLATE Pure Tac**

### **Typical Characteristics (cont'd.)**

Oxidation Stability 100 Hours	2 psi
Base Fluid Properties	
Saybolt Viscosity @ 100°F	6,500 SUS
Saybolt Viscosity @ 210°F	182 SUS
Kinematic Viscosity @ 40°C	1187 cSt
Kinematic Viscosity @ 100°C	39 cSt
Flash Point, °F/°C	420/216
Fire Point, °F/°C	470/243
Pour Point, °F/°C	25/-4

### **Statement of Usage:**

“These compounds may be used on food, beverage and pharmaceutical processing and packaging equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures and as a lubricant for machine parts and equipment in locations in which there is potential exposure of the lubricated part to food, beverage, pharmaceutical and related packaging equipment. The amount used should be the minimum required to accomplish the desired technical effect on the equipment.”

<b><u>Packaging Available</u></b>	<b><u>Part No.</u></b>
35 lb. pail	L0236-035
120 lb. drum	L0236-039
415 lb. drum	L0236-040
Case, 40-14½ oz. cartridges	L0236-098

### **\*NSF H-1 Registration No. 043649**

(Meets USDA 1998 Guidelines)

\*Authorized by NSF for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

\*NSF – National Sanitation Foundation

Manufactured with ingredients that comply with FDA 21 CFR 178.3570.