



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**

Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**

Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**

Phone: 1-800-733-4755

**LUBRIPLATE SUPER GPO OILS 30 & 40**

**LUBRIPLATE SUPER GPO OILS** are formulated with a chemistry that has a proven record for excellent performance in both naturally aspirated and turbocharged diesel engines.

**LUBRIPLATE SUPER GPO OILS provide:**

Easy starting and fast circulation  
High temperature thermal stability  
Superior anti-rust and bearing corrosion protection  
Good protection from low temperature sludge and varnish formations  
High film strength for superior valve train wear protection in both conventional valve trains and overhead cams  
Good compatibility with nitrile, silicone and polyacrylate elastomers minimizing seal leakage problems  
Outstanding anti-oxidant properties providing resistance to oil thickening  
Excellent compatibility with fluoroelastomer clutch friction materials, thus extending transmission life  
Improved piston cleanliness, reduced ring and cylinder wear  
Reduced bearing wear, thus increasing bearing life  
Reduced oil consumption  
Improved power shift transmission performance  
Fuel economy

**LUBRIPLATE SUPER GPO OILS 30 & 40 are recommended for:**

API CF/SL/SJ

ACEA02 - E2/B4/B3/A2

Volvo VDS

RVI RLD

MB 228.2 / MB 229.0

Man 271 / Man 3275

MTU Oil Category 1

(over)

**LUBRIPLATE SUPER GPO OILS 30 & 40**

**Typical Tests**

<b><u>SAE No.</u></b>	<b><u>GPO 30</u></b>	<b><u>GPO 40</u></b>
Viscosity, Saybolt Universal		
SUS @ 210°F	69	79
SUS @ 100°F	586	749
Viscosity, Kinematic		
cSt @ 100°C	12.5	15.5
cSt @ 40°C	108	157
Viscosity Index	100	103
API Gravity	27.2	26.5
Color	L-6	L-6
Flash Point, °F/°C	435/224	445/229
Fire Point, °F/°C	465/241	480/249
Pour Point, °F/°C	-30/-34	-15/-26
Cold Crank Simulator,		
cP @ -20°C (ASTM D-5293)	-----	-----
Borderline Pumping Viscosity		
cP @ -25°C (ASTM D-4684)	-----	-----

**LUBRIPLATE SUPER GPO OILS 30 & 40 are available in the following:**

	<b><u>PART NUMBERS</u></b>	
<b><u>Packaging Available</u></b>	<b><u>GPO 30</u></b>	<b><u>GPO 40</u></b>
Carton, 12/1 Quart Plastic Bottles	L0749-054	-----
5 Gallon Pail	L0749-060	L0752-060
55 Gallon Drum	L0749-062	L0752-062