



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**

Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**

Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**

Phone: 1-800-733-4755

**LUBRIPLATE SUPER GPO 10W-30**

**LUBRIPLATE SUPER GPO OILS** are formulated with a chemistry that has a proven record for excellent performance in both naturally aspirated and turbocharged diesel engines. **LUBRIPLATE SUPER GPO** multi-vis oils are extremely shear stable over long operating periods.

**LUBRIPLATE SUPER GPO OILS provide:**

Easy starting and fast circulation  
High temperature thermal stability  
Superior anti-rust and bearing corrosion protection  
Good protection from low temperature sludge and varnish formations  
High film strength for superior valve train wear protection in both conventional valve trains and overhead cams  
Good compatibility with nitrile, silicone and polyacrylate elastomers minimizing seal leakage problems.  
Outstanding anti-oxidant properties providing resistance to oil thickening  
Excellent compatibility with fluoroelastomer clutch friction materials, thus extending transmission life  
Improved piston cleanliness, reduced ring and cylinder wear  
Reduced bearing wear, thus increasing bearing life  
Reduced oil consumption  
Improved power shift transmission performance  
Fuel economy

**LUBRIPLATE SUPER GPO 10W-30 is recommended for:**

API CI-4/CH-4/CG-4/CF-4/CF/SL/SJ

ACEA02 - E5/E3/B4/B3/A3/A2

EO-M+

Cat ECF-1

Cummins CES 20,0071/2/6/7/8

Volvo VDS / VDS-2 / VDS-3

Global DHD-1

MB 228.3 / MB 229.1

Man 271 / Man 3275

MTU Oil Category 2

RVI RLD

(over)

**LUBRIPLATE GPO 10W-30**

**Typical Tests**

<b><u>SAE No.</u></b>	<b><u>GPO 10W-30</u></b>
Viscosity, Saybolt Universal	
SUS @ 210°F	64
SUS @ 100°F	322
Viscosity, Kinematic	
cSt @ 100°C	11.4
cSt @ 40°C	69
Viscosity Index	140
API Gravity	29.1
Color	L-6
Flash Point, °F/°C	400/204
Fire Point, °F/°C	430/221
Pour Point, °F/°C	-40/-40
Cold Crank Simulator,	
cP @ -20°C (ASTM D-5293)	-----
Borderline Pumping Viscosity	
cP @ -25°C (ASTM D-4684)	-----

**LUBRIPLATE SUPER GPO 10W-30 is available in the following:**

<b><u>Packaging Available</u></b>	<b><u>Part Number</u></b>
Carton, 12/1 Quart Plastic Bottles	L0754-054
5 Gallon Pail	L0754-060
55 Gallon Drum	L0754-062