



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE SUPER GPO 10W-30 Motor Oil

LUBRIPLATE Super GPO 10W-30 Motor Oil is an engine oil developed for use in four-stroke cycle diesel engines designed to meet 2007 and later EPA on-highway exhaust emissions standards. It is specially formulated to protect exhaust after treatment devices such as diesel particulate filters (DPFs), diesel oxidation catalysts (DOCs) and selective catalytic reduction (SCR) systems. It is backward serviceable for use in pre-2007 diesel engines and may be used in mixed fleets with both diesel and gasoline-fueled vehicles.

Benefits

- Excellent protection for newer low-emission diesel engines and older diesel engines
- Specially formulated to protect exhaust after treatment devices
- Protects against particulate filter plugging
- Excellent soot control for protection against abrasive wear and soot-induced oil thickening
- Excellent resistance to viscosity and thermal breakdown at high temperatures
- Protects against sludge and varnish formation
- Protects against rust, bearing corrosion and wear
- Good resistance to foaming and aeration

Meets or exceeds the following specifications:

- API Service CJ-4
- API Service CI-4
- API Service CH-4
- API Service CG-4
- API Service SM
- EO-M plus
- Caterpillar ECF-3, ECF-2, ECF-1
- Cummings CES 20081

LUBRIPLATE Super GPO 10W-30 Motor Oil:

Typical Tests

SAE Grade	10W-30
Specific Gravity @ 60°F	0.872
Density, lbs/gal @ 60°F	7.26
Color, ASTM D1500	4.0
Flash Point (COC), °C (°F)	227 (441)
Pour Point, °C (°F)	-45 (-49)
Viscosity, Kinematic	
cSt @ 40°C	80.0
cSt @ 100°C	12.0
Viscosity Index	146
Cold Cranking Viscosity, cP @ (°C)	6,200 (-25)
High-Temp/High-Shear Viscosity, cP @ 150°C	3.6
Sulfated Ash, ASTM D874, wt %	0.97
Total Base Number (TBN), ASTM D2896	8.4
Zinc, wt %	0.121

LUBRIPLATE Super GPO 10W-30 Motor Oil is available in the following:

Packaging Available

Part Numbers

Carton, 12/1 Quart Plastic Bottles	L0754-054
5 Gallon Pail	L0754-060
55 Gallon Drum	L0754-062