



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE SUPER GPO 15W-40

LUBRIPLATE SUPER GPO OILS are formulated with a chemistry that has a proven record for excellent performance in both naturally aspirated and turbocharged diesel engines. **LUBRIPLATE SUPER GPO** multi-vis oils are extremely shear stable over long operating periods.

LUBRIPLATE SUPER GPO OILS provide:

Easy starting and fast circulation
High temperature thermal stability
Superior anti-rust and bearing corrosion protection
Good protection from low temperature sludge and varnish formations
High film strength for superior valve train wear protection in both conventional valve trains and overhead cams
Good compatibility with nitrile, silicone and polyacrylate elastomers minimizing seal leakage problems.
Outstanding anti-oxidant properties providing resistance to oil thickening
Excellent compatibility with fluoroelastomer clutch friction materials, thus extending transmission life
Improved piston cleanliness, reduced ring and cylinder wear
Reduced bearing wear, thus increasing bearing life
Reduced oil consumption
Improved power shift transmission performance
Fuel economy

LUBRIPLATE SUPER GPO 15W-40 is recommended for:

API CI-4/CH-4/CG-4/CF-4/CF/SL/SJ

ACEA02 - E5/E3/B4/B3/A3/A2

Mack EO-N PP, EO-N, EO-M+

Cat ECF-1

Cummins CES 20,0071/2/6/7/8

Volvo VDS / VDS-2 / VDS-3

Global DHD-1

MB 228.3 / MB 229.1

Man 271 / Man 3275

MTU Oil Category 2

RVI RLD

(over)

LUBRIPLATE GPO 15W-40

Typical Tests

<u>SAE No.</u>	<u>GPO 15W-40</u>
Viscosity, Saybolt Universal	
SUS @ 210°F	69
SUS @ 100°F	548
Viscosity, Kinematic	
cSt @ 100°C	15.4
cSt @ 40°C	111.3
Viscosity Index	141
API Gravity	33.7
Color	L-4
Flash Point, °F/°C	465/241
Fire Point, °F/°C	520/271
Pour Point, °F/°C	-35/-37
Cold Crank Simulator,	
cP @ -20°C (ASTM D-5293)	5122
Borderline Pumping Viscosity	
cP @ -25°C (ASTM D-4684)	16874

LUBRIPLATE SUPER GPO 15W-40 is available in the following:

<u>Packaging Available</u>	<u>Part Number</u>
Carton, 12/1 Quart Plastic Bottles	L0753-054
Carton, 2/2½ Gallon Jugs	L0753-055
5 Gallon Pail	L0753-060
55 Gallon Drum	L0753-062