



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE Super 345 Motor Oil SAE 5W-30

LUBRIPLATE Super 345 Motor Oil SAE 5W-30 is a superior-quality, high detergent automotive engine oil specially formulated with synthetic base stocks and mineral oil for better fuel economy and to reduce harmful emissions while meeting and exceeding the OEM's stringent lubrication requirements of today's engines. **LUBRIPLATE Super 345 Motor Oil SAE 5W-30** can be used in passenger cars, light trucks and sport utility vehicles under all operating conditions. **LUBRIPLATE Super 345 Motor Oil SAE 5W-30** is formulated using an advanced additive package that provides maximum protection against wear, rust, corrosion, thermal breakdown, acid formation, reduces sludge build up and the formation of sludge and varnish deposits.

Benefits:

- Friction-modified for improved fuel economy
- Protects against sludge and varnish formation
- Helps protect emissions system
- Minimized rust and corrosion
- Good low temperature pour point
- Excellent resistance to viscosity and thermal breakdown at high temperatures

Meets or exceeds the following specifications:

- API Service Category SN, SM, SL, SJ, SH, SG, SF, SE, SD or SC
- Energy Conserving, ILSAC GF-5
- Meets or exceeds the requirements of MIL-1-46152E
- Ford WSS-M2C929-A (5W30)
- DaimlerChrysler DC MS-639N, MS-6395L
- GM 6094M specification (5W30), GM 9986231 (SAE 5W30)
- Toyota service fill requirements for 5000 mile service intervals

(Over)

LUBRIPLATE Super 345 Motor Oil SAE 5W-30:

Typical Tests

Viscosity, Kinematic cSt @ 100°C	10.5
6600 cP max @ Deg C	-35
SAE Grade	5W30
Viscosity Index	155
Specific Gravity	0.872
Flash Point, COC °F	400
Pour Point, °C (min)	-35

LUBRIPLATE Super 345 Motor Oil SAE 5W-30 is available in the following packaging:

Packaging Available

Part Numbers

Case, 12/1 Quart Plastic Jugs	L0732-054
5 Gallon Pail	L0732-060
55 Gallon Drum	L0732-062

Printed in USA
Revised 11/1/11