



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

LUBRIPLATE FMO-45

*NSF H1 & 3H Registered

“This product is certified OU Kosher Pareve”

“This product is Halal certified”

LUBRIPLATE FMO-45 is a very light technical mineral oil meeting NSF H-1 requirements. This designation allows the use of this lubricant on machine parts where incidental contact with the edible product is possible.

Typical tests for LUBRIPLATE FMO-45 are as follows:

Saybolt Viscosity @ 100°F	40 SUS
Kinematic Viscosity @ 40°C	4.0 cSt
Flash Point	265°F/129°C
Pour Point	30°F/-1°C
Color	L2.0
API Gravity	42.5
NSF Rating	H-1
ISO Grade	5

Packaging Available

Part No.

5-Gallon Pail	L0737-060
55-Gallon Drum	L0737-062

***NSF H1 & 3H Registration No. 122688**
(Meets USDA 1998 Guidelines)

NSH H1 - Authorized by NSF for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

NSF 3H - These products are acceptable for use as Release Agents (3H) on grills, ovens, loaf pans, boning benches, chopping boards or other hard surfaces in contact with meat and poultry food products to prevent food from adhering during processing.

*NSF – National Sanitation Foundation

Manufactured with ingredients that comply with FDA 21 CFR 178.3570.

Printed in USA
Revised 7/9/10