



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE TURBINE OILS

LUBRIPLATE Turbine Oils have been specifically formulated for steam turbine applications. In addition to offering protection against oxidation, rust and foam, LUBRIPLATE Turbine Oils also readily separate from moisture.

The LUBRIPLATE Turbine Oil 32 meets the requirements of General Electric Specification GEK-46506D.

<u>Typical Tests</u>	<u>32</u>	<u>46</u>
Viscosity		
SUS @ 100°F	152	216
SUS @ 210°F	44	47.9
cSt @ 40°C	32	42.1
cSt @ 100°C	5.4	6.4
ISO VG	32	46
Viscosity Index, ASTM D-2270	133	100
Flash Point, ASTM D-92	390°F/199°C	435°F/224°C
Pour Point, ASTM D-97	-10°F/-23°C	0°F/-18°C
Water Content	<0.01%	<0.01%
Rust Test, ASTM D-665	Pass; No Rust	Pass; No Rust
Specific Gravity	0.864	0.867
Neutralization Value	0.20 mg KOH/g (max)	0.20 mg KOH/g (max)
TOST, ASTM D-943	> 2,000 Hours	> 10,000 Hours
Color	L-1.5	L-1.0
<u>Packaging Available</u>		
55 Gallon Drum	L0942-062	L0943-062