



EXECUTIVE OFFICE: NEWARK, NJ 07105
PHONE: 973-589-9150 FAX: 973-589-4432
MIDWEST OFFICE: TOLEDO, OH 43605
PHONE: 419-691-2491 FAX: 419-693-3806
TECHNICAL SERVICE PHONE NO. 800-347-5343

FISKE's 716 EP-1 Moly

FISKE's 716-EP-1 Moly is a lithium based, multi-purpose, non-corrosive, extreme pressure, water resistant lubricant containing molybdenum disulfide.

| <u>Typical Tests</u> | <u>716 EP-1 Moly</u> |
|-------------------------|-----------------------------------|
| Type of Base | Lithium 12-Hydroxy Stearate |
| Worked Penetration | 310/340 |
| N.L.G.I. No. | 1 |
| Worked Penetration | |
| 60 Strokes | 311 |
| 10,000 Strokes | 320 |
| 100,000 Strokes | 344 |
| ASTM Dropping Point, °F | 370 |
| Timken EP Test, OK Load | 45 lbs. |
| Mineral Oil Viscosity | |
| SUS @ 210°F | 103 |
| SUS @ 100°F | 1350 |
| Pour Point, °F | +5 |
| Flash Point, °F | 405 |
| Water Resistant | Yes |

Contains Technical Fine Molybdenum Disulfide (Mos2).