



Sales, Service & Distribution Center  
 Newark, NJ 07105  
 Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center  
 Toledo, OH 43605  
 Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support  
 Phone: 1-800-733-4755

**FISKE's AW Hydraulic Oils – ISO 32, 46, 68 & 100**

\*NSF H2 Registered ISO 32, 46 & 68  
 \*NSF H2 Registered ISO 100 (Pending)

The FISKE's AW Hydraulic Oils are high performance, anti-wear products for all types of hydraulic and recirculating systems found on industrial, construction and automotive equipment. They are fortified with rust and oxidation inhibitors and have outstanding demulsibility. The anti-wear additive package helps minimize the formation of sludge and other corrosive by-products which can cause reduction of pump life, filter blocking and interfere with efficient hydraulic power transfer. All four FISKE's AW Hydraulic Oils have been designed to meet Cincinnati Milacron and Vickers hydraulic oil specifications. Their high aniline points help prolong seal life.

<b><u>Typical Tests</u></b>	<b><u>AW-32</u></b>	<b><u>AW-46</u></b>	<b><u>AW-68</u></b>	<b><u>AW-100</u></b>
Viscosity cSt @ 40°C	29.43	41.91	65.29	103.4
Viscosity SUS @ 100°F	154	213	314	479
Viscosity SUS @ 210°F	43.5	47.5	53.8	62.0
Viscosity Index	97	99	103	84

Flash Point	405°F/207°C	410°F/210°C	430°F/221°C	510°F/266°C
Fire Point	445°F/230°C	450°F/232°C	470°F/243°F	555°F/291°C
Pour Point	-25°F/-32°C	-20°F/-29°C	-10°F/-23°C	-5°F/-21°C

Gravity	32.6	32.1	31.2	27.1
---------	------	------	------	------

Color	L-2.5	L-2.5	L-2.5	L-2.5
-------	-------	-------	-------	-------

<b><u>Packaging Available</u></b>	<b><u>AW-32</u></b>	<b><u>AW-46</u></b>	<b><u>AW-68</u></b>	<b><u>AW-100</u></b>
5-Gallon Pail	F0400-060	F0401-060	F0402-060	F0403-060
55-Gallon Drum	F0400-062	F0401-062	F0402-062	F0403-062

<b>*NSF H2 Registration No's</b>	<b><u>141055</u></b>	<b><u>141056</u></b>	<b><u>141057</u></b>	<b><u>Pending</u></b>
----------------------------------	----------------------	----------------------	----------------------	-----------------------

\*These products are acceptable as lubricants where there is no possibility of food contact (H2) in and around food processing areas. Such compounds may be used as lubricants, release agents, or antirust films on equipment and machine parts in locations in which there is no possibility of the lubricant or lubricated part contacting edible products.