



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE SPRAY-LUBE "A"

MULTI-PURPOSE WHITE LITHIUM SPRAY

DESCRIPTION

LUBRIPLATE Spray-Lube "A" is a multi-purpose, white, medium density lithium grease with exceptional penetrating qualities. The convenient aerosol can, which sprays like a fluid but congeals to a grease, puts an end to messy open cans and dirty grease forever. The handy extension spout gets to those hard-to-reach places allowing pinpointing of the lube to minimize waste.

ADVANTAGES

Unlike many lubricants, LUBRIPLATE Spray-Lube "A" is unaffected by moisture, most chemicals and acids, and will not run, wash off or dry up. Excellent where no grease fittings exist and where tolerances are close and where longer lasting lubrication is desirable.

LUBRIPLATE Spray-Lube "A" may be safely used within temperature ranges from -10°F to 275°F.

APPLICATIONS

A few of the hundreds of possible uses are:

Home: Toys, guns, reels, clocks, appliances, skates, hinges, faucet valves, window regulators, garage doors and openers, bicycles, mowers, garden tools, recliners, drawer slides, shop tools, automotive hood and truck releases, ashtray slides, door hinges, cables, battery terminals, accelerator hinges

Office: Typewriters, filing cabinets, adding machines and calculators, duplicating equipment, swivel chairs

Industry: Lightly-loaded open gears, cams, couplings, slides, bearings, bushings, lift truck masts, controls

Recreation: Boat fittings and linkage, golf carts, pin setters, campers, trailers, motorcycles, snowmobiles

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Type of Soap		Lithium
Worked Penetration Range @ 77°F	ASTM D 217	310 - 340
NLGI No.		1
ASTM Dropping Point	ASTM D 566	380°F/193°C
Mineral Oil Viscosity: SUS @ 100°F	ASTM D-2161	750
cSt @ 40°C	ASTM D-445	135
Color	Visual	White

PACKAGING AVAILABLE

Carton, 12/11 oz. Aerosol Cans

Part No.

L0034-063

