



THE HEAVY-DUTY TACKY RED GREASE

THAT STICKS WITH YOU
UNDER THE TOUGHEST
CONDITIONS

LUBRIPLATE® LTR-2

This rugged, thick/tacky/adhesive, multi-purpose, extreme pressure grease can withstand higher temperatures than traditional lithium greases. The advanced, zinc free additive package provides outstanding anti-wear protection. This NLGI Number 2 density, multi-purpose grease is recommended for a wide variety of heavy-duty applications. Red in color.

LITHIUM COMPLEX Formulation for High-Temperature Applications

ZINC FREE Contains an Advanced, High Performance, Zinc Free Anti-Wear Additive Package.

NLGI NO. 2 GRADE Multi-Purpose For a Wide Range of Applications



Lubriplate®
Lubricants

Newark, NJ 07105 / Toledo, OH 43605 / 800-733-4755
www.lubriplate.com / LubeXpert@lubriplate.com



Backed By: **Lubriplate®**
ESP

Extra Services Package

Equipment Surveys / Tech Support / Training
Color Coded Lube Charts & Machine Tags
Lubrication Software / Follow-Up Oil Analysis

Lubriplate® LTR-2 / Heavy-Duty, Tacky, Red, Lithium Complex Grease.

LUBRIPLATE LTR-2 is a RED lithium complex grease that can be used for a variety of industrial, automotive and heavy-duty construction applications. This rugged, extreme pressure lubricant can withstand higher operating temperatures than traditional lithium multi-purpose greases as well as most lithium complex greases.

LUBRIPLATE LTR-2 is tacky, adhesive and very water resistant. The film strength and shear stability of this product is exceptional resulting in wear reduction and long lubricant life.

Specifications

Type of Base	Lithium Complex
NLGI Grade (ASTM D-217)	2
Appearance	Tacky, Red, Smooth
Base Oil Kinematic Viscosity cSt @ 40°C / @ 100°C	460 / 31
ISO Viscosity Grade	460
Dropping Point (ASTM D-2265)	505°F / 263°C
Four Ball Wear (ASTM D-2266)	40 kg. 1200 rpm, 1 hr. @ 167°F 0.52 mm
Four Ball EP Test (ASTM D-2596)	620 kg. OK Load
Oil Separation (ASTM D-1742)	0.11 % by weight
Corrosion (ASTM D-130)	3 hours 1a
Water Washout (ASTM D-1264)	@ 175°F <5 %
Bearing Corrosion (ASTM D-1743)	Pass, No Corrosion
Lincoln Ventmeter Testing	77° 500 psig / 30° 750 psig / 0° Not Pumpable

Interchange / Crossover Recommendations

Chevron Ultra Duty No. 2	Lubriplate LTR-2
Citgo Mystic JT-6	Lubriplate LTR-2
Lubrication Engineers Almatek 1232	Lubriplate LTR-2
Lubrication Engineers Almaplex 1275	Lubriplate LTR-2
Lubrication Engineers Almagard 3752	Lubriplate LTR-2
Lubrication Engineers Multiplex 4622	Lubriplate LTR-2
Shell Retinax No. 2	Lubriplate LTR-2
Texaco Starplex No. 2	Lubriplate LTR-2
Texas Refining Company TRC-Red	Lubriplate LTR-2

Packaging Availability / Part Number

Cartridges - 14.5 OZ / 411 g	Part Number L0167-098
Pails - 35 LB / 15.9 kg	Part Number L0167-035
Quarter Drums - 120 LB / 54 kg	Part Number L0167-039
Drums - 420 LB / 191 kg	Part Number L0167-040



Lubriplate®
Lubricants

Backed By:



Extra Services Package

- Complimentary Equipment Surveys • Tech Support
- Lubrication Software • Machinery Tags
- Follow-Up Lubricant Analysis • Training

Newark, NJ 07105 / Toledo, OH 43605 / 1-800-733-4755
www.lubriplate.com / LubeXpert@lubriplate.com