



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**  
Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**  
Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**  
Phone: 1-800-733-4755

## **LUBRIPLATE Super GPO 15W-40 CJ-4**

**LUBRIPLATE Super GPO 15W-40 CJ-4** is a heavy duty, extra high performance multi-grade engine oil that provides excellent protection in diesel fuel and gasoline engines over a wide range of operating conditions and performance demands. Compounded with detergents, dispersants, wear control elements, anti-oxidants, corrosion inhibitors and foam suppressant additive. Extremely resistant to development of high temperature deposits and low temperature sludge clogging, inhibit ring deposit formation, reduces engine wear associated with increased soot levels and improved oil consumption control. Suitable for use in almost all foreign and domestic engines, gasoline or diesel, naturally aspirated or turbocharged. Always consult your owner's manual for proper application.

**LUBRIPLATE Super GPO 15W-40 CJ-4** is formulated to offer superior performance in today's high performance, fuel efficient, low-emission diesel and gasoline engines. It is recommended for use in naturally aspirated, turbo-charged, or super charged diesel, gasoline and propane engines, including those featuring EGR or other technologies for emissions control. Meets API Service Classification CJ-4, CI-4 PLUS, CI-4, CH-4, CG-4, CF-4, CF/SL, SJ, Caterpillar ECF-3, Cummins CES 20081, 20078, 20076, 20072, 20071, Mack EO-O Premium Plus 07, Mack EO-N Premium Plus, EO-M Plus, EO-M, Mercedes Benz 228.3, 228.1, Man 3275, Volvo VDS-4, VDS, DDC Power Guard Oil Specification 93K218, 93K214, Detroit Diesel 7 SE 270 (4-Stroke Engines), DDC/MTU Type 1 engine performance, DHD-1, DH-1, ACEA E5 and E3. Can also be used in applications recommending Allison C-4 and Caterpillar TO-2 specifications.

### **Benefits:**

- Superior soot handling and wear control
- Excellent EGR emission control performance
- Outstanding oxidation stability
- Excellent low temperature properties helps speed cold starts
- Universal product for consolidation of products

(Over)

**LUBRIPLATE Super GPO 15W-40 CJ-4 is recommended for:**

API CJ-4, CI-4 PLUS, CH-4, CG-4, CF-4, CF/SL, SJ, SH  
Caterpillar ECF-3, ECF-1 & ACERT Engines  
Cummins CES 20081, 20078, 20077, 20076, 20072, 20071  
Mack EO-O Premium Plus 03, EO-N Premium Plus, EO-M Plus, EO-M  
Mercedes Benz 228.3, 228.1  
MAN 271, 3275  
DHD-1, DH-1, ACEA E5 and E3  
Volvo VDS-4, VDS-2, VDS  
Detroit Diesel 93K218, 93K214, 7SE270  
DDC/MTU Series Type 1 (DHD-1, DH-1, ACEA E5 and E3)  
Allison C-4, Caterpillar TO-2

**Typical Tests**

Viscosity @ 40°C, cSt (D445)	115
Viscosity @ 100°C, cSt (D445)	15.2
Viscosity Index (D2270)	137
Pour Point °C / °F (D97)	-39 / -38
Flash Point °C / °F (D92)	213 / 415
Neutralization No., TBN (D2896)	8.4
Sulfated Ash, wt. % (D874)	0.97

**LUBRIPLATE Super GPO 15W-40 CJ-4 is available in the following:**

<b><u>Packaging Available</u></b>	<b><u>Part Number</u></b>
Carton, 12/1 Quart Plastic Bottles	L0755-054
Carton, 2/2½ Gallon Jugs	L0755-055
5 Gallon Pail	L0755-060
55 Gallon Drum	L0755-062