



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

#### Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

#### Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

#### Sales and Tech Service Support

Phone: 1-800-733-4755

## PRODUCT DATA

# LUBRIPLATE CP-8A GEAR OIL

## DESCRIPTION

LUBRIPLATE CP-8A Gear Oil is formulated to be in accordance with AGMA Specification 8A Comp. Gear Oil.

## APPLICATIONS

LUBRIPLATE CP-8A Gear Oil will not mix with or dissolve in water. This product is recommended for use in cone drives and double-enveloping worm gear drives where such an oil is required.

## ADVANTAGES

LUBRIPLATE CP-8A Gear Oil is a non-EP oil, but is manufactured with 3 to 10% acidless tallow as required to meet AGMA Specifications.

## Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity: SUS @ 100°F	ASTM D-2161	4950
cSt @ 40°C	ASTM D-445	950
SUS @ 210°F	ASTM D-2161	230
cSt @ 100°C	ASTM D-445	47
Viscosity Index, Min.	ASTM D-2270	95
Flash Point	ASTM D-92	550°F/288°C
Fire Point	ASTM D-92	600°F/316°C
Pour Point	ASTM D-97	35°F/2°C
AGMA No.		8A Comp.
ISO VG		1000

## PACKAGING AVAILABLE

35 lb. Pail  
120 lb. Drum  
415 lb. Drum

## Part No.

L0141-035  
L0141-039  
L0141-040

