



Fiske Brothers Refining Co.
DBA Lubriplate Lubricants
Co.
1500 Oakdale Avenue
P.O. Box 8038 Station "A"
Toledo, OH 43605
United States
July 20, 2023

Registration may be verified at
nsfwhitebook.org



A handwritten signature in blue ink, appearing to read 'S. Cole'.

Samuel Cole
NSF Nonfood Compounds
Registration Program
Company No: N03353

Certificate of Registration

Fiske Brothers Refining Co. DBA Lubriplate Lubricants Co. has achieved Registration status for LUBRIPLATE SYNXTREME FG-0/220 to the NSF International Registration Guidelines for Proprietary Substances and Nonfood Compounds (2022) .

LUBRIPLATE SYNXTREME FG-0/220


Category Code: H1

NSF Registration No. 149637

This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas. Such compounds may be used on food processing equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures, and as a lubricant for machine parts and equipment in locations in which there is a potential exposure of the lubricated part to food. The amount used should be the minimum required to accomplish the desired technical effect on the equipment. If used as an anti-rust film, the compound must be removed from the equipment surface by washing or wiping, as required to leave the surface effectively free of any substance which could be transferred to food being processed.

This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas. Such compounds may be used on food processing equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures, and as a lubricant for machine parts and equipment in locations in which there is a potential exposure of the lubricated part to food. The amount used should be the minimum required to accomplish the desired technical effect on the equipment. If used as an anti-rust film, the compound must be removed from the equipment surface by washing or wiping, as required to leave the surface effectively free of any substance which could be transferred to food being processed.

This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas. Such compounds may be used on food processing equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures, and as a lubricant for machine parts and equipment in locations in which there is a potential exposure of the lubricated part to food. The amount used should be the minimum required to accomplish the desired technical effect on the equipment. If used as an anti-rust film, the compound must be removed from the equipment surface by washing or wiping, as required to leave the surface effectively free of any substance which could be transferred to food being processed.



Registration of this product is current when the NSF Registration Mark and Category Code appear on the product label reviewed by NSF, and the Registered product name is in the NSF White Book (www.nsfwhitebook.org).

Listing of all registered nonfood compounds by NSF International is not an endorsement of those compounds or of any performance or efficacy claims made by the manufacturer.