



EXECUTIVE OFFICE: NEWARK, NJ 07105
PHONE: 973-589-9150 FAX: 973-589-4432
MIDWEST OFFICE: TOLEDO, OH 43605
PHONE: 419-691-2491 FAX: 419-693-3806
TECHNICAL SERVICE PHONE NO. 800-347-5343

FISKE's 400 Class "B"

FISKE's 400 Class "B" is a lithium combination type product of an NLGI No.1 Grade, non-corrosive, extreme pressure lubricant with an ASTM Dropping Point in excess of 400°F. and a good working cold test down to -40°F. This product is water resistant and resistant to a large degree to most other types of contamination. In addition, this product is very well suited to compatibility with a wide range of plastics. The light viscosity oil in this product makes it ideal for many types of high speed applications where fluid-friction must be kept to a minimum.

Typical tests on FISKE's 400 Class "B" are as follows:

Type of Thickener	Lithium Combination
Worked Penetration @ 77°F.	310 - 340
NLGI Number	1
ASTM Dropping Point, °F.	410
Non-Corrosive, Extreme Pressure & Lubricity Additives	Yes
Color	Tan
Mineral Oil Viscosity SUS @ 100°F.	180 - 220
4 Ball Weld Point (Kg.)	200+
Water Washout (ASTM D-1264) @ 40°C (104°F)	1.71%
Operating Temperature Range	-40°F. to 300°F.