

FISKE BROTHERS REFINING COMPANY

NEWARK, NEW JERSEY 07105 . TOLEDO, OHIO 43605

FISKE'S STAMPING OIL 7

Description: Colorless, odorless, low viscosity organic lubricating fluid.

Uses: A light duty stamping and forming oil that will largely evaporate after use, usually

eliminating the need for a subsequent cleaning operation. **Stamping Oil 7** is especially useful for stamping aluminum, galvanized steel, tinplate, copper, brass,

terneplate and pre-painted steel.

TYPICAL CHARACTERISTICS:

| Viscosity @ 100°F., SUS/cSt | 31/1 |
|-----------------------------|--------|
| Flash Point °F./°C. | 135/57 |
| Fire Point °F./°C. | 140/60 |
| API Gravity | 50.6 |
| Sulfur | No |
| Active Sulfur | No |
| Chlorine | No |
| Fatty Material | Yes |
| Color | 0.0 |
| | |

Advantages:

- Compounded for enhanced wetting ability
- Lubricates like mineral oil
- Non-staining to all metals
- Evaporates after use -- leaves slight oily film that is hardly noticeable
- Does not affect painted surfaces
- Safe flash point (130°F.)
- Contains no sulfur or chlorine
- Meets the FDA requirements of a material that may be used as a surface lubricant in the manufacture of metallic articles that contact food

Application: Spray, brush, dip, wipe-on and felt pads.

Caution:

This product should be used with adequate ventilation and without frequent

bodily

contact or prolonged inhalation of vapors. Keep away from flames.

(Over)

Stamping Oil 7 is available in the following:

Packaging Available
5 gallon pail
55 gallon drum

Part Number F0560-060