



ISO-9001 Registered Quality System.

**Sales, Service & Distribution Center**  
 Newark, NJ 07105  
 Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**  
 Toledo, OH 43605  
 Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**  
 Phone: 1-800-733-4755

**PRODUCT DATA**

**LUBRIPLATE "100" SERIES**  
 No.'s 100,105,107,110 & 115

**DESCRIPTION**

The LUBRIPLATE "100" Series Products are excellent water-resistant lubricants designed for plain bearings, cams, slides and similar applications up to operating temperatures of 150°F.

**APPLICATIONS & ADVANTAGES**

**LUBRIPLATE No. 100 and No. 105** are excellent lubricants for coating engine parts when assembling either a new or rebuilt engine. They are excellent rust preventive greases.

**LUBRIPLATE No. 107** is an outstanding concrete form release agent because it does not stain the concrete. Also, an excellent anti-seize compound for the threads on bolts which hold metal forms.

**LUBRIPLATE No. 110** is recognized as an outstanding brake lubricant.

**LUBRIPLATE No. 115** is the ideal water pump lubricant. These lubricants offer a long lasting film of protection for light duty applications.

**STORAGE RECOMMENDATIONS**

- ⇒ Products should be stored between 40°F-120°F
- ⇒ Products should be stored in a dry covered environment
- ⇒ Products should not be stored in warm, direct sunlight
- ⇒ Improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.



**Typical Test Data**

PROPERTY	TEST METHOD	TYPICAL RESULTS				
		100	105	107	110	115
Type of Base	ASTM	Calcium	Calcium	Calcium	Calcium	Calcium
NLGI No.		00	0	1	2.5	4
Worked Penetration	D-217	Semi-Fluid	355/385	310/340	235/260	175/205
Unworked Penetration: 30 gram cone @ 77°F	D-217	365/375	***	***	***	***
Dropping Point	D-2265	170°F 77°C	170°F 77°C	180°F 82°C	190°F 88°C	210°F 99°C
<b>Viscosity:</b>						
SUS @ 100°F	D-2161	300	300	300	300	300
cSt @ 40°C	D-445	58	58	58	58	58
Color	Visual	Off-White	Off-White	Off-White	Off-White	Off-White
Character		Smooth	Smooth	Smooth	Smooth	Smooth

**PACKAGING AVAILABLE**

- Carton, 12 - 16 oz. Plastic Tubs
- Carton, 4 - 6 lb. Plastic Tubs
- Carton 4 - 7 lb. Jugs
- Carton 12 - 2 lb. Plastic Bottles
- 35 lb. Pail
- 120 lb. Quarter Size Drum
- Full Size Drum
- Carton, 36 - 3/8 oz. Tubes
- Carton, 36 - 1.75 oz. Tubes
- Carton, 36 - 10 oz. Plastic Tubes:

- C-105 Outboard Gear
- C-105 Motor Assembly

**PACKAGING AVAILABLE**

- Carton, 12 - 16 oz. Plastic Tubs
- Carton, 4 - 6 lb. Plastic Tubs
- 35 lb. Pail
- 120 lb. Quarter Size Drum
- Full Size Drum

**No. 100**

- \*\*\*
- \*\*\*
- L0031-007
- L0031-013
- L0031-035
- L0031-039
- L0031-040
- \*\*\*
- \*\*\*
- \*\*\*
- \*\*\*
- \*\*\*
- \*\*\*
- \*\*\*

**No. 105**

- L0034-004
- L0034-005
- \*\*\*
- \*\*\*
- L0034-035
- L0034-039
- L0034-040
- L0034-079
- L0034-086
- L0034-092
- L0034-094

**No. 107**

- L0036-004
- L0036-005
- \*\*\*
- \*\*\*
- L0036-035
- L0036-039
- L0036-040
- \*\*\*
- \*\*\*
- \*\*\*
- \*\*\*

**No. 110**

- L0037-004
- L0037-005
- L0037-035
- L0037-039
- \*\*\*

**No. 115**

- L0040-004
- L0040-005
- L0040-035
- L0040-039
- L0040-040