



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**  
Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**  
Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**  
Phone: 1-800-733-4755

## PRODUCT DATA

# LUBRIPLATE MULTI-LUBE "A"

## DESCRIPTION

LUBRIPLATE Multi-Lube "A" is an anhydrous calcium, NLGI No. 2 grade, non-corrosive, extreme pressure, water resistant, multi-purpose lubricant with a workable range of -20°F to 210°F.

## APPLICATIONS

LUBRIPLATE Multi-Lube "A" is recommended for both plain and anti-friction bearings, cams, slides and open gears. This lubricant is especially suited for wet applications as it is very resistant to moisture and many other liquid contaminants.

## STORAGE RECOMMENDATIONS

- ⇒ Products should be stored between 40°F-120°F
- ⇒ Products should be stored in a dry covered environment
- ⇒ Products should not be stored in warm, direct sunlight
- ⇒ Improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.



## Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Type of Base		Anhydrous Calcium
Worked Penetration	ASTM D-217	265 to 295
NLGI No.		2
Dropping Point	ASTM D566	280°F/138°C
Mineral Oil Viscosity SUS @ 100°F	ASTM D-2161	500
cSt @ 40°C	ASTM D-445	95
Oxidation Stability	ASTM D-942	Excellent
Color	Visual	Beige
Character	Visual	Smooth

## PACKAGING AVAILABLE

## Part No.

35 lb. Pail	L0183-035
120 lb. Quarter Size Drum	L0183-039
430 lb. Full Size Drum	L0183-040