



ISO-9001 Registered Quality System.

Sales, Service & Distribution CenterNewark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432**Manufacturing, Sales, Service & Distribution Center**Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806**Sales and Tech Service Support**

Phone: 1-800-733-4755

PRODUCT DATA**LUBRIPLATE SPECIAL AUTO-MARINE GREASE****DESCRIPTION**

LUBRIPLATE Special Auto-Marine Grease is an NLGI 2 polymer type lubricant specifically designed for automotive and marine applications of all types. This lithium 12-hydroxy stearate grease is extremely shear stable and resistant to both fresh and salt water, making it the ideal lubricant for all marine and automotive needs.

APPLICATIONS

Marine uses include all pressure fitting applications including boat trailer wheel bearings, winch gears, deck machinery, ground tackle and turn-buckles.

Automotive applications include chassis, king pins, steering knuckles, bucket pins, ball joints and universal joints.

ADVANTAGES

- ⇒ Excellent extreme pressure/anti-wear properties
- ⇒ Extremely shear stable
- ⇒ High temperature characteristics
- ⇒ Very good sealing properties to keep out water and dirt
- ⇒ Outstanding resistance to fresh and salt water
- ⇒ Tenacious and adhesive to increase stay-put properties

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Type of Base		Lithium 12-Hydroxy Stearate
Worked Penetration	ASTM D-217	265 - 295
NLGI No.		2
ASTM Dropping Point	ASTM D-566	400°F+/205°C+
Mineral Oil Viscosity: SUS @ 100°F	ASTM D-2161	1250
cSt @ 40°C	ASTM D-445	237
SUS @ 210°F	ASTM D-2161	95
cSt @ 100°C	ASTM D-445	19
Timken E.P. Test: OK Load	ASTM D-2783	60 lbs.
Four Ball E.P. Test: OK Load	ASTM D-2783	370 kg.
Load Wear Index	ASTM D-2266	64.3
Corrosion Prevention	ASTM D-1743	1,1,1
Copper Corrosion	ASTM D-130	1a
Oxidation Stability	ASTM D-942	3 psi/100 hours
Water Washout	ASTM D-1264	1.5%
Appearance	Visual	Tacky, Beige

PACKAGING AVAILABLECarton, 12/16 oz. Plastic Tubs
Carton, 40/14½ oz. Cartridges**Part No.**L0206-004
L0206-098