



ISO-9001 Registered Quality System.

**Sales, Service & Distribution Center**

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**

Phone: 1-800-733-4755

**PRODUCT DATA****LUBRIPLATE Poly HP-2****DESCRIPTION**

LUBRIPLATE Poly HP-2 is a polyurea-thickened lubricating grease formulated for improved bearing protection and longer electric motor life.

**APPLICATIONS**

Fortified with corrosion and oxidation inhibitors, LUBRIPLATE Poly HP-2 is an excellent choice for the lubrication and protection of high-speed electric motor bearings; as well as other industrial applications:

- ⇒ Electric Motor Bearings
- ⇒ High Temperature Bearing Applications
- ⇒ Pump Bearings

**ADVANTAGES**

LUBRIPLATE Poly HP-2 is recommended by major bearing and electric motor manufacturers.

LUBRIPLATE Poly HP-2 under mechanical stress performs better, compared to competitor polyurea-based electric motor greases.

LUBRIPLATE Poly HP-2 performs very well in high temperature applications.

**Typical Test Data**

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Thickener		Polyurea
Worked Penetration: 60 Strokes	ASTM D-217	265
NLGI No.		2
Worked Penetration: 100,000 Strokes	ASTM D-217	40 (Change)
Dropping Point	ASTM D-2265	500°F/260°C
Oxidation Stability/Grease Life	ASTM D-3336	1,000 hrs.+
Four Ball Wear: 40kg,1200RPM, 75°C,1hr.	ASTM D-2266	0.45
Mineral Oil Viscosity: SUS @ 100°F	ASTM D-2161	650
cSt @ 40°C	ASTM D-445	128
Appearance	Visual	Red
Texture	Visual	Smooth/Buttery
Copper Corrosion	ASTM D-130A	1b
Corrosion Resistance	ASTM D-1743	Pass
Oil Separation	ASTM D-1742	<3.0%

**PACKAGING AVAILABLE**

35 lb. Pail

120 lb. Quarter Size, Drum

Carton, 40/14 oz. Cartridges

**Part No.**

L0191-035

L0191-039

L0191-098

