



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE No. 405 CUTTING OIL

HEAVY-DUTY DARK CUTTING OIL

DESCRIPTION

The unusually high extreme pressure content of this active sulfur product provides optimum results in prolonged tool life, improved finish, more accurate cuts, greater production, and reduced labor cost.

ADVANTAGES

It is an outstanding dark pipe threading oil.

APPLICATIONS

LUBRIPLATE No. 405 Cutting Oil is especially recommended for use on low or high carbon steels, alloys and stainless steels where difficult conditions of service are encountered.

Not recommended for brass, bronze, copper or aluminum.



Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity: SUS/cSt @ 100°F	ASTM D-2161/ D-445	225/48
Flash Point	ASTM D-92	380°F/193°C
Fire Point	ASTM D-92	400°F/204°C
API Gravity	ASTM D-287	25.7
Sulfur		Yes
Active Sulfur		Yes
Chlorine		Yes
Fatty Material		Yes
Color	Visual	Dark Brown

PACKAGING AVAILABLE

Part No.

Carton 4/1 Gallon Jugs
5 Gallon Pail
55 Gallon Drum

L0587-057
L0587-060
L0587-062