



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**  
Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**  
Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**  
Phone: 1-800-733-4755

## PRODUCT DATA

# LUBRIPLATE METAL WORKING FLUID

### DESCRIPTION

LUBRIPLATE Metal Working Fluid is a specially developed product suitable for a variety of metal working applications.

### ADVANTAGES

- ⇒ Does not contain Fluorocarbons
- ⇒ Does not contain 1,1,1 Trichloroethane

### APPLICATIONS

The 12-ounce aerosol can, including extension spout, makes it the ideal lubricant for:

- ⇒ Drilling
- ⇒ Sawing
- ⇒ Tapping
- ⇒ Grinding
- ⇒ Thread Chasing
- ⇒ Pipe Cutting
- ⇒ Filing
- ⇒ Nut Busting

### TYPICAL TEST DATA

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity: SUS @ 100°F	ASTM D-2161	150
cSt @ 40°C	ASTM D-445	32
Viscosity: SUS @ 210°F	ASTM D-2161	45
cSt @ 100°C	ASTM D-445	6
ISO Grade		32
SAE Grade		10
Flash Point	ASTM D-92	310°F/154°C
Fire Point	ASTM D-92	350°F/177°C
Pour Point	ASTM D-97	-40°F/-40°C
Specific Gravity	ASTM D-4052	0.906
Color	ASTM D-1500	L-3

### PACKAGING AVAILABLE

Carton 12/12 oz. Aerosol Cans

### Part No.

L0185-063

