

ISO-9001 Registered Quality System. ISO-21469 Compliant. Sales, Service & Distribution CenterNewark, NJ 07105Phone: 973-589-9150Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center Toledo, OH 43605 Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE No. 4 & No. 8



LUBRIPLATE No. 4 and LUBRIPLATE No. 8 are specially (formulated oils) strictly for industrial bearing and gear case applications. These oils are formulated with special lubricity agents and tackiness additives.

ADVANTAGES

LUBRIPLATE No. 4 and LUBRIPLATE No. 8 have exceptional film strength, and "stay put" or "clinging" qualities. These oils also provide positive protection against rust and corrosion.

APPLICATIONS

LUBRIPLATE No. 4 is an SAE 90 gear lubricant. LUBRIPLATE No. 4 is recommended extensively for medium to medium slow speed, heavy-duty bearings, enclosed gear cases, gear head motors, heavy way lubricant and wherever an oil of this viscosity is required for industrial applications.

LUBRIPLATE No. 8 is an SAE 140 gear lubricant. LUBRIPLATE No. 8 is ideal for all types of enclosed gears where an SAE 140 gear lubricant is required. LUBRIPLATE No. 8 is recommended for the lubrication of slow speed, heavy-duty bearings. LUBRIPLATE No. 8 is recommended as an excellent worm gear lubricant providing that necessary film follow-up so necessary in this type of application.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*	
		No. 4	No. 8
Viscosity: SUS @ 100°F	ASTM D-2161	854	2300
cSt @ 40°C	ASTM D-445	162	432
SUS @ 210°F	ASTM D-2161	72	142
cSt @ 100°C	ASTM D-445	13	28
API Gravity	ASTM D-287	23.5	27.1
Flash	ASTM D-92	420°F/216°C	435°F/224°C
Fire Point	ASTM D-92	450°F/232°C	515°F/268°C
Pour Point	ASTM D-97	-20°F/-29°C	0°F/-18°C
Tackiness Additives		Yes	Yes
Color	ASTM D-1500	3+	4+
Approximate SAE No.		90	140
ISO Grade		150	460
AGMA No.		4	7

PACKAGING AVAILABLE	No. 4	No. 8
Carton, 4/7 lb. Jugs	L0011-007	L0014-007
Carton, 12/2 lb. Plastic Bottles	L0011-013	L0014-013
35 lb. Pail	L0011-035	L0014-035
120 lb. Quarter Size Drum	L0011-039	L0014-039
415 lb. Full Size Drum	L0011-040	L0014-040