



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE HYDRAULIC JACK OIL

DESCRIPTION

LUBRIPLATE Hydraulic Jack Oil is a heavy duty, high pressure, anti-wear, and non-corrosive hydraulic fluid.

APPLICATIONS

Recommended for hydraulic jacks and similar applications.

ADVANTAGES

- ⇒ Fluid zinc for anti-wear properties.
- ⇒ High natural V.I. for stable viscosities throughout a wider operating temperature.
- ⇒ High aniline point for controlled seal-swelling characteristics.
- ⇒ Rust and corrosion resistant properties.
- ⇒ Chemical and mechanical stabilities.
- ⇒ Foam suppression properties.
- ⇒ Good heat transfer properties.
- ⇒ Thermal oxidation stability.
- ⇒ Good demulsibility properties.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity: SUS/cSt @ 100°F/40°C	ASTM D-2161/D-445	160/31
Viscosity: SUS/cSt @ 210°F/100°C	ASTM D-2161/D-445	46/6
Viscosity Index	ASTM D-2270	136
API Gravity	ASTM D-287	31.6
Color	ASTM D-1500	L2.0
Pour Point	ASTM D-97	-30°F/-34°C
Flash Point	ASTM D-92	415°F/213°C
Fire Point	ASTM D-92	440°F/227°C

PACKAGING AVAILABLE

Carton 12/1 Quart Plastic Jugs
Carton 4/1 Gallon Plastic Jugs
5 Gallon Pail
16 Gallon Drum
55 Gallon Drum

Part No.

L0768-054
L0768-057
L0768-060
L0768-061
L0768-062