



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE SYNFLUSH

DESCRIPTION

LUBRIPLATE SYNFLUSH is a premium quality, pure synthetic fluid designed to clean and dissolve varnish/deposits found in rotary screw and reciprocating type air compressors while the compressor is in operation. It is compatible with petroleum/mineral oils as well as all LUBRIPLATE Synthetic Compressor Fluids and most other synthetic fluids. Contact us for compatibility verification.

APPLICATIONS

LUBRIPLATE SYNFLUSH is also designed for flushing compressors converting from petroleum/mineral oil to synthetic fluids. The flushing procedure removes the remaining petroleum oil that is unable to be removed by draining alone as well as cleaning the compressor prior to introducing the new synthetic fluid.

LUBRIPLATE SYNFLUSH can also be used to clean hydraulic systems, gearboxes and reducers, FRL's (Airline Oilers) and close looped circulating oil systems.

LUBRIPLATE SYNFLUSH is not intended for automotive/diesel applications such as cleaning fuel injectors or crankcases.

Contact LUBRIPLATE @ 800-347-5343 for procedural assistance.

ADVANTAGES

- ⇒ Removes varnish and carbon deposits, which greatly improves compressor efficiency and life expectancy.
- ⇒ Compatible with petroleum base oils as well as all LUBRIPLATE Synthetic Compressor Fluids.
- ⇒ Can be used in its pure form in all types of air compressors up to 500 hours.
- ⇒ Contains no hazardous chemicals.
- ⇒ Offers excellent thermal and oxidative stability.
- ⇒ Provides excellent solubility, solvency, and cleaning capabilities.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity cSt @ 40°C	ASTM D-445	27
Viscosity cSt @ 100°C	ASTM D-445	5.35
Viscosity Index	ASTM D-2270	135
Flash Point	ASTM D-92	243°C
Fire Point	ASTM D-92	282°C
Pour Point	ASTM D-97	-60°C
Specific Gravity	ASTM D-4052	0.909

PACKAGING AVAILABLE

Carton 12/1 Quart Plastic Jugs
Carton 4/1 Gallon Plastic Jugs
5 Gallon Pail
55 Gallon Drum

Part No.

L0962-054
L0962-057
L0962-060
L0962-062

