



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE “OIL WELL” IN A BOTTLE
NON-AEROSOL HAND PUMP SPRAY BOTTLE

DESCRIPTION

LUBRIPLATE “Oil Well” in a Bottle is a lubricating, penetrating, moisture displacement, “wet start” and cleansing fluid designed for a multitude of applications.

APPLICATIONS

Typical uses include:

- ⇒ Chains
- ⇒ Cables
- ⇒ Locks
- ⇒ Hinges
- ⇒ Latches
- ⇒ Slides
- ⇒ Rusty Nuts & Bolts
- ⇒ Moisture Displacement

ADVANTAGES

The moisture displacement properties of LUBRIPLATE “Oil Well” in a Bottle make it an excellent choice for “wet start” applications.

LUBRIPLATE “Oil Well” in a Bottle possesses exceptional rust-proofing properties. Its light viscosity promotes excellent wetting characteristics which will quickly spread to cover the applied area.

LUBRIPLATE “Oil Well” in a Bottle hand pump spray does not contain Fluorocarbons or 1,1,1-Trichloroethane. This non-aerosol formula is non-flammable and does not contain any solvents or propellants which will give you 100% lubricant for your money.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity SUS @ 100°F	ASTM D-2161	45
Viscosity cSt @ 40°C	ASTM D-445	6
Viscosity SUS @ 210°F	ASTM D-2161	31
Viscosity cSt @ 100°C	ASTM D-445	1.5
Flash Point	ASTM D-92	280°F/138°C
Fire Point	ASTM D-92	305°F/152°C
Color	ASTM D-1500	5
Appearance	Visual	Clear to Hazy

PACKAGING AVAILABLE

Carton, 12/14 oz. Plastic Bottles

Part No.

L0188-067

