



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE FMO-45

"This product is certified OU Kosher Pareve"
"This product is Halal certified"

*NSF International H-1 & 3H Registered
NSF ISO21469 Certification

DESCRIPTION

LUBRIPLATE FMO-45 is manufactured with pure USP white mineral oil, it is NSF 3H registered for direct contact, and NSF H1 registered for incidental contact

STORAGE RECOMMENDATIONS

- ⇒ Products should be stored between 40°F-120°F
- ⇒ Products should be stored in a dry covered environment
- ⇒ Products should not be stored in warm, direct sunlight
- ⇒ Improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS
Specific Gravity @ 25°C		0.851
Kinematic Viscosity @ 40°C	ASTM D-445	10 cSt
Saybolt Viscosity @ 100°F	ASTM D-2161	60 SUS
Colour, Saybolt		+30
Pour Point, °C (°F)		- 24 (-11.2)
Flash Point, COC, °C		175
Flash Point, COC, °F		347

PACKAGING AVAILABLE

- 5 Gallon Pail
- 55 Gallon Drum

Part No.

- L0737-060
- L0737-062



***NSF International H1 & 3H Registration No.**
(Meets former USDA 1998 Guidelines)

122688

*Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

NSF 3H registered products are acceptable for use as Release Agents (3H) on grills, ovens, loaf pans, boning benches, chopping boards or other hard surfaces in contact with meat and poultry food products to prevent food from adhering during processing.

Manufactured with ingredients that comply with FDA 21 CFR 178.3570.