



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE SUPER GPO 40 MOTOR OIL

DESCRIPTION

Meets or exceeds the following specifications:

- ⇒ API CF-2
- ⇒ API CF (obsolete)
- ⇒ MIL-PRF-2104G
- ⇒ Detroit Diesel 2-stroke cycle engines, Oil Type 1 (1.0 % max. Sulfated ash)
- ⇒ Arvin Meritor, Dana Spicer and Eaton Fuller manual transmissions

APPLICATIONS

LUBRIPLATE Super GPO 40 Motor Oil is a high-quality diesel engine oil designed for use in a wide variety of applications, including off-highway diesel equipment, farm machinery, marine engines, 2-stroke cycle diesel engines (in the appropriate viscosity grades) and mixed commercial fleets. It may be also used in some heavy duty manual transmissions in trucks and busses.

ADVANTAGES

- ⇒ Excellent soot control for protection against abrasive wear and soot-induced oil thickening
- ⇒ Protects against sludge and varnish formation
- ⇒ Protects against scuffing and wear
- ⇒ Protects against rust and bearing corrosion
- ⇒ Good resistance to foaming and aeration
- ⇒ Low-ash content to minimize the formation of ash deposits and helps keep intake ports clean



Typical Test Data

| PROPERTY | TEST METHOD | TYPICAL RESULTS* |
|-----------------------|-------------|------------------|
| Viscosity cSt @ 40°C | ASTM D-445 | 149 |
| Viscosity cSt @ 100°C | ASTM D-445 | 15.4 |
| SAE Grade | | 40 |
| Viscosity Index | ASTM D-2270 | 106 |
| Pour Point °F | ASTM D-5950 | -27 |
| TBN (min) | ASTM D-2896 | 8.1 |
| Zinc, wt % | ASTM D 5185 | 0.109 |
| Sulfated Ash % wt | ASTM D-874 | 1.0 |

PACKAGING AVAILABLE

5 Gallon Pail
55 Gallon Drum

Part No.

L0752-060
L0752-062