



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**  
Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**  
Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**  
Phone: 1-800-733-4755

**PRODUCT DATA**

**LUBRIPLATE FG Proofer Chain Oil**

“These products are certified OU Kosher Pareve”  
“These products are Halal certified”

\*NSF International H-1 Registered  
NSF ISO21469 Certification

**DESCRIPTION**

LUBRIPLATE FG PROOFER CHAIN OIL has been designed specifically for bakery proofer chains, especially those operating in humid and/or wet environments. This product utilizes premium quality USP white mineral oils, advanced polymers, and a unique additive package to provide adhesiveness and excellent anti-wear capabilities. LUBRIPLATE FG PROOFER CHAIN OIL provides long life to bakery proofer chains especially those operating in high humidity and excessively wet environments. LUBRIPLATE FG PROOFER CHAIN OIL is NSF H1 Food Grade Registered which greatly improves plant food safety.

**APPLICATIONS**

- ⇒ Bakery Proofer Chains
- ⇒ Chains or any lubricated machine component operating in wet, humid, or corrosive environments.
- ⇒ Can be applied by spray or drip oilers.

**ADVANTAGES**

- ⇒ Superior Anti-Wear Protection increases chain pin and bushing life.
- ⇒ Adhesiveness reduces drippage allowing for the potential extension of relubrication intervals which reduces usage, as well as this unique waterproof tacky product provides increased protection from water and chemical corrosion on all metal surfaces.
- ⇒ Rust and Corrosion Inhibitors enhance the resistance of the chain components to the effects of water and chemical exposure.
- ⇒ NSF H1 Food Grade Registered.
- ⇒ Kosher and other certifications

**STORAGE RECOMMENDATIONS**

- ⇒ Products should be stored between 40°F-120°F
- ⇒ Products should be stored in a dry covered environment
- ⇒ Products should not be stored in warm, direct sunlight
- ⇒ Improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.

**Typical Test Data**

PROPERTY	TEST METHOD	TYPICAL RESULTS*
<b>Viscosity:</b>		
SUS @ 100°F	ASTM D-2161	510
cSt @ 40°C	ASTM D-445	103
SUS @ 210°F	ASTM D-2161	67
cSt @ 100°C	ASTM D-445	12
Viscosity Index	ASTM D-2270	108
API Gravity	ASTM D-287	30.2
Flash Point	ASTM D-92	410°F/ 210°C
Fire Point	ASTM D-92	450°F/ 232°C
Pour Point	ASTM D-97	-5°F/ -21°C

**PACKAGING AVAILABLE**

- 55 Gallon Drum
- 5 Gallon Pail

**PART NUMBER**

- L0734-062
- L0734-060

\*NSF International H-1 Registration No.'s  
(Meets former USDA 1998 Guidelines)

162776

\*Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

“Lubriplate Proofer Chain Oil contains no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011”.



Nonfood Compounds  
H1 Registered  
ISO 21469 Certified

PAREVE

HALAL